

# Product Bulletin



Dow AgroSciences

Dow AgroSciences LLC

9330 Zionsville Road

Indianapolis, IN 46268-1054 USA

## Garlon® XRT

EPA Reg. No. 62719--553

### Sec 2(ee) Recommendation<sup>†</sup>

For Distribution and Use Only in the States of Kansas and Oklahoma

### Aerial Applications for Control of Weed and Brush Species

#### ATTENTION

<sup>†</sup> This recommendation is made as permitted under FIFRA 2(ee) and has not been submitted to or approved by the EPA.

- It as a violation of Federal law to use this product in a manner inconsistent with its labeling.
- Read and follow all applicable directions for use, precautions, and limitations on the product label attached to the container for Garlon XRT herbicide.

#### Directions for Use

Garlon XRT may be applied aerially by helicopter or fixed wing aircraft.

Follow all applicable use directions, precautions, and limitations found on the main label for Garlon XRT.

#### Aerial Application

For aerial application on rights-of-way or other areas near susceptible crops, apply through a Microfoil<sup>†</sup> or Thru-Valve<sup>†</sup> boom or other drift control application equipment, and/or use an agriculturally labeled drift control additive. If a spray thickening agent is used, follow all use recommendations and precautions on the product label. Spray only when the wind velocity is low (follow state regulations). Avoid application during air inversions.

#### Spray Drift Management

Avoiding spray drift at the application site is the responsibility of the applicator. The interactions of many equipment- and weather-related factors determine the potential for spray drift. The applicator and the grower are responsible for considering all of these factors when making decisions.

The following drift management requirements must be followed to avoid off-target drift movement from aerial applications.

1. The distance of the outer most operating nozzles on the boom must not exceed 3/4 the length of the wingspan or rotor.
2. Nozzles must always point backward parallel with the air stream and never be pointed downward more than 45 degrees.

Where states have more stringent regulations, they must be observed.

The applicator should be familiar with and take into account the information in the Aerial Drift Reduction Advisory found on the main label for Garlon XRT. Refer to main label for Garlon XRT for additional information about avoiding injurious spray drift, spray drift management requirements, and aerial drift reduction advisories.

† Reference within this label to a particular piece of equipment produced by or available from other parties is provided without consideration for use by the reader at its discretion and subject to the reader's independent circumstances, evaluation, and expertise. Such reference by Dow AgroSciences is not intended as an endorsement of such equipment, shall not constitute a warranty (express or implied) of such equipment, and is not intended to imply that other equipment is not available and equally suitable. Any discussion of methods of use of such equipment does not imply that the reader should use the equipment other than is advised in directions available from the equipment's manufacturer. The reader is responsible for exercising its own judgment and expertise, or consulting with sources other than Dow AgroSciences, in selecting and determining how to use its equipment.

®™ Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow

R426-001

Issued: 03/22/18

Initial printing