# SAFETY DATA SHEET



### 1. Identification

Product identifier R-900 Other means of identification None.

Recommended use Ag Product - Adjuvant

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Wilbur-Ellis Company LLC
Address 16300 Christensen Rd. Ste 135

Tukwila, WA 98188

**United States** 

**Telephone** Branded Products Information (800) 500-1698

E-mail SDS@wilburellis.com

Emergency phone number Chemtrec - Domestic (800) 424-9300 Chemtrec - International +1 703-741-5970

# 2. Hazard(s) identification

Physical hazards Flammable liquids Category 3

Health hazards Not classified.
Environmental hazards Not classified.
OSHA defined hazards Not classified.

Label elements



Signal word Warning

**Hazard statement** Flammable liquid and vapor.

**Precautionary statement** 

Prevention Keep away from heat, sparks, open flames, and hot surfaces. - No smoking. Keep container

tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting, and process equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves, eye protection, and face protection.

Response IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water. In

case of fire: Use appropriate media as described in Section 5 for extinction.

Storage Store in a well-ventilated place. Keep cool.

**Disposal** Dispose of contents and container in accordance with government regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

## 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Butyl Alcohol		71-36-3	20 - < 30
Other components below reportable levels			70 - < 80

Percentage ranges of composition to protect confidentiality or due to batch variation.

Material name: R-900 SDS US

### 4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Take off immediately all contaminated clothing. Rinse skin with water. Get medical attention if Skin contact

irritation develops and persists.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Get medical attention if irritation develops and persists.

Rinse mouth. Get medical attention if symptoms occur. Ingestion

Most important

symptoms/effects, acute and delayed

Direct contact with eyes may cause temporary irritation.

Indication of immediate medical attention and special treatment needed

General information

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital.

Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

# 5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods General fire hazards Use standard firefighting procedures and consider the hazards of other involved materials.

Flammable liquid and vapor.

## 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Stop the flow of material, if this is without risk. Use water spray to reduce vapors or divert vapor cloud drift. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

# **Environmental precautions**

# 7. Handling and storage Precautions for safe handling

Avoid discharge into drains, water courses or onto the ground.

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Material name: R-900 SDS US Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

# 8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components Value Type **PEL** Butyl Alcohol (CAS 71-36-3) 300 mg/m3 100 ppm **US. ACGIH Threshold Limit Values** Value Components Type Butyl Alcohol (CAS 71-36-3) TWA 20 ppm **US. NIOSH: Pocket Guide to Chemical Hazards** Components **Type** Value Butyl Alcohol (CAS 71-36-3) Ceiling 150 mg/m3

**Biological limit values** 

No biological exposure limits noted for the ingredient(s).

**Exposure guidelines** 

US - California OELs: Skin designation

Butyl Alcohol (CAS 71-36-3)

Can be absorbed through the skin.

**US - Minnesota Haz Subs: Skin designation applies** 

Butyl Alcohol (CAS 71-36-3) Skin designation applies.

**US - Tennessee OELs: Skin designation** 

Butyl Alcohol (CAS 71-36-3)

Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Butyl Alcohol (CAS 71-36-3)

Can be absorbed through the skin.

Appropriate engineering

controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

50 ppm

Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

Skin protection

**Hand protection** Wear appropriate chemical resistant gloves.

Other Wear suitable protective clothing.

**Respiratory protection** If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not

been established), an approved respirator must be worn.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

### 9. Physical and chemical properties

**Appearance** 

Physical state
Form
Liquid.
Color
Not available.
Odor
Not available.
Odor threshold
Not available.
PH
Not available.
Melting point/freezing point
Not available.

Material name: R-900 SDS US

779 Version #: 02 Revision date: 09-26-2017 Issue date: 02-23-2016

Initial boiling point and boiling Not available.

range

Flash point 135.0 °F (57.2 °C)
Evaporation rate Not available.
Flammability (solid, gas) Not available.
Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

(0/)

Not available.

Explosive limit - lower (%) Not available.
Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

**Density** 7.76 lb/gal

Flammability class Combustible II estimated

Specific gravity 0.93

# 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

**Incompatible materials** Strong oxidizing agents. Alkaline metals.

**Hazardous decomposition** 

products

No hazardous decomposition products are known.

## 11. Toxicological information

# Information on likely routes of exposure

**Inhalation** Prolonged inhalation may be harmful.

Skin contact

No adverse effects due to skin contact are expected.

Eye contact

Direct contact with eyes may cause temporary irritation.

**Ingestion** Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and

toxicological characteristics

Direct contact with eyes may cause temporary irritation.

#### Information on toxicological effects

**Acute toxicity** 

Material name: R-900 SDS US

**Species Test Results** Components

Butyl Alcohol (CAS 71-36-3)

Acute Dermal

LD50 Rabbit 3430 mg/kg, 24 Hours

4.24 ml/kg, 24 Hours

Oral

LD50 Rat 4360 mg/kg

2.83 ml/kg

Prolonged skin contact may cause temporary irritation. Skin corrosion/irritation Serious eye damage/eye Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Not available. Respiratory sensitization

Skin sensitization This product is not expected to cause skin sensitization.

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity - single exposure

Not classified.

Specific target organ

toxicity - repeated

exposure

Not classified.

Not available. Aspiration hazard

**Chronic effects** Prolonged inhalation may be harmful.

12. Ecological information

**Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available. Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents and container in accordance with government regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Empty containers should be taken to an approved waste handling site for recycling or disposal. Contaminated packaging

Since emptied containers may retain product residue, follow label warnings, if applicable, even

after container is emptied.

Material name: R-900 SDS US

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

# 14. Transport information

### DOT

Not regulated as dangerous goods.

**DOT BULK** 

**BULK** 

NA1993 **UN number** 

**UN proper shipping name** Combustible Liquid, N.O.S. (Isopropanol)

Transport hazard class(es)

Combustible Liquid Class

Label(s) 3 Packing group Ш

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IATA

UN1993 **UN** number

UN proper shipping name Flammable liquid, n.o.s. solution (Isopropanol)

Transport hazard class(es)

3 Class Subsidiary risk Packing group Ш **Environmental hazards** No. 3L **ERG Code** 

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

FLAMMABLE LIQUID, N.O.S. SOLUTION (Isopropanol)

Passenger and cargo

aircraft

Allowed with restrictions.

Not established.

Cargo aircraft only Allowed with restrictions.

**IMDG** 

**UN** number UN1993

UN proper shipping name

Transport hazard class(es)

3 **Class** Subsidiary risk Ш Packing group

**Environmental hazards** Marine pollutant

No. F-E, S-E

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

**DOT Bulk packaging type** 



Material name: R-900 SDS US



# 15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Butyl Alcohol (CAS 71-36-3) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No

Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

 Chemical name
 CAS number
 % by wt.

 N-BUTYL ALCOHOL
 71-36-3
 20 - < 30</td>

## Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Butyl Alcohol (CAS 71-36-3) Low priority

**US state regulations** 

**US. California Proposition 65** 

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

### 16. Other information, including date of preparation or last revision

**Issue date** 02-23-2016 **Revision date** 09-26-2017

Version # 02

NFPA ratings Health: 1

Flammability: 3
Instability: 0

Material name: R-900 SDS US

779 Version #: 02 Revision date: 09-26-2017 Issue date: 02-23-2016

# NFPA ratings



### Disclaimer

This information was developed from information on the constituent materials. No warranty is expressed or implied regarding the completeness or continuing accuracy of the information contained herein, and Wilbur-Ellis disclaims all liability for reliance thereon. The user should satisfy himself that he has all current data relevant to his particular use.

Material name: R-900 SDS US