

Foaminator® Dry

NFPA HAZARD RATING

U.S. TRANSPORT SUMMARY

0	Least		
1	Slight	1	Health
2	Moderate	0	Flammability
3	High	0	Reactivity
4	Severe		

Not regulated as a hazardous material for ground transport. (See Section 14 for additional information)

SECTION 1: IDENTIFICATION

Product Name: Foaminator® Dry
EPA Registration #: Exempt
Product ID/Unity #: 10051059

Common Name: Dry antifoam powder Chemical Description: Antifoam powder

Recommended Uses: Agricultural Adjuvant. See product label for complete list of recommended uses and use sites.

Restrictions for Use: See product label for information regarding restrictions on the use of this product.

Manufactured For: WINFIELD SOLUTIONS, LLC

Non-Emergency Business Inquiries: 1-855-494-6343

P. O. Box 64589 St. Paul, MN 55164-0589

Mon – Fri 8am – 5pm (Central Standard Time)

MEDICAL EMERGENCY TELEPHONE NUMBER: 1-877-424-7452 (24hrs)

FOR EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT, CALL:

CHEMTREC 1-800-424-9300 (24 hours)

SECTION 2: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: White powder with a mild odor. Causes eye irritation. Causes mild skin irritation. May cause respiratory irritation.

POTENTIAL HEALTH EFFECTS:

Eyes: Causes moderate but temporary irritation to the eyes.

Skin: Prolonged or repeated exposure may cause mild skin irritation. **Inhalation**: May be harmful if inhaled causing respiratory irritation.

Ingestion: May be harmful if swallowed.

Preexisting Conditions: Pre-existing respiratory conditions may be aggravated by exposure to dust.

Chronic Health Effects: None known.

Carcinogenicity NTP: Not listed IARC: Not listed OSHA: Not listed

OSHA HCS 2012 CLASSIFICATION: Eye Irritant Category 2B; Specific Organ Toxicity – Single Exposure – Category 3

SIGNAL WORD: WARNING

HAZARD STATEMENTS:

Causes eye irritation.

May cause respiratory irritation.



Percent of product with unknown toxicity: 0%

PRECAUTIONARY STATEMENTS:

Prevention: Wash hands thoroughly after handling. Avoid breathing dust. Use only outdoors in a well-ventilated area. Response: If in eyes: Rinse cautiously with water for 15 minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. If eye irritation persists get medical attention. **If inhaled:** Remove person to fresh air and keep comfortable for breathing. Call a poison control center (1-877-424-7452) or doctor for treatment advice if you

feel unwell.

Continued on next page

Storage: Store in a well-ventilated and locked place. Keep container tightly closed.

Disposal: Dispose of contents/container in accordance with Federal, state and local regulations.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS				
Ingredient	% (wt)	CAS Reg. #		
Proprietary mixture of polydimethylsiloxane and foam suppressing aids and inert materials	100.0%	*		
*Ingredients not specifically listed are non-hazardous and/or are considered to be confidential business information under 29 CFR 1910.1200(i).				

See Section 8 for exposure limits.

SECTION 4: FIRST AID MEASURES

Inhalation: Remove person from contaminated area to fresh air and assist breathing as needed. Seek medical attention

or call a poison control center for treatment advice

Ingestion: Seek medical attention or call a poison control center immediately. Do not induce vomiting unless told to do

so by a poison control center or doctor. Do not give anything by mouth to an unconscious person.

Eyes: Flush eyes with clean water for at least 15 minutes. Lift eyelids to facilitate irrigation. If present, remove

contact lenses after 5 minutes and continue rinsing. Seek medical attention if irritation persists.

Skin: Remove contaminated clothing and wash before re-using them. Wash exposed skin with soap and water.

Seek medical attention if skin becomes irritated.

SECTION 5: FIRE FIGHTING MEASURES

Suitable Extinguishing Media: Use water spray, foam, dry chemical, or carbon dioxide (CO2).

Unsuitable Extinguishing Media: Water jet.

Special Fire Fighting Procedures: Wear NIOSH/MSHA approved self-contained breathing apparatus and full bunker gear. Dike area to prevent runoff and contamination of water sources. Dispose of fire control water later. Avoid breathing vapors; keep upwind. Water may be ineffective in firefighting. Use water spray/fog for cooling containers and firefighters.

Hazardous Combustion Products: Can generate formaldehyde at temperatures of approximately 300°F and above. Can also produce carbon oxides, sulfur oxides, nitrogen oxides and crystalline silica.

Unusual Fire and Explosion Hazards: Heat may build pressure and rupture closed containers, spreading fire and increasing the risk of injury.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Refer to Section 8 for personal protective equipment to be worn during containment and clean-up of a spill involving this product.

Environmental Precautions: Keep spilled product from entering nearby sewers or waterways.

Methods for Containment: Contain spilled liquid by diking area with sand or earth.

Methods for Clean-up: Cover contained spill with an inert absorbent material such as sand, vermiculite or other appropriate material. Vacuum, scoop or sweep up material and place in a container for disposal. Do not place spilled material back in original container.

Other Information: No other information available.

SECTION 7: HANDLING AND STORAGE

Handling: Ensure adequate ventilation. Immediately clean up spills that occur during handling. Keep containers closed when not in use. Practice good hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.

Storage: Store in cool, dry area away from children, feed and food products in an area away from incompatible substances. Protect packaging from physical damage. Protect from exposure to fire.

Minimum Storage Temperature: Not determined

Other Precautions: Consult Federal, state and local laws and regulations pertaining to storage.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION					
Exposure Guidelines					
Component:	OSHA PEL	ACGIH TLV	NIOSH REL		
No components have exposure guidelines.					
Respiratory Protection: Seek professional advice prior to respirator selection and use. Follow OSHA respirator regulations (29					
CFR 1910.134) and, if necessary, wear an OSHA/NIOSH-approved respirator for general particulates.					

Engineering Controls: Local Exhaust: Provide general or local exhaust ventilation systems to maintain airborne

concentrations below OSHA PELs or other specified exposure limits. Local exhaust ventilation is

preferred.

Protective Gloves: Wear chemically protective gloves to prevent repeated exposure to the skin.

Eye Protection: To avoid contact with eyes, wear chemical goggles or face shield and safety glasses. Contact lenses are not eye protective devices. An emergency eyewash or water supply should be readily accessible to the work area.

Other Protective Clothing or Equipment: Wear long-sleeve shirt, long pants and shoes plus socks to prevent prolonged or repeated skin contact.

Work/Hygienic Practices: Never eat, drink, nor use tobacco in work areas. Practice good hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES						
Physical State:	Solid	Specific Gravity (H ₂ O=1):	Not applicable			
Vapor Pressure (mm Hg):	Not determined	Density (lbs/gallon):	Not applicable			
Vapor Density (Air=1):	Not determined	Melting Point/Freezing Point:	Not determined			
Solubility in Water (wt %):	Soluble	Boiling Point/Range:	Not determined			
Viscosity:	Not determined	pH (1% Solution):	6.5 – 8.5			
Appearance and odor:	White powder with a mild odor	Flash Point:	>200°F			

SECTION 10: STABILITY AND REACTIVITY

Reactivity: None known.

Chemical Stability: Product is stable at ambient temperature and pressure, under normal storage and handling.

Possibility of Hazardous Reactions: None known.

Conditions to Avoid: Avoid heat and open flame. Isolate from strong oxidizing agents

Incompatible Materials: Oxidizing agents

Hazardous Decomposition Products: Can generate formaldehyde at temperatures of approximately 300°F and above. Can

also produce carbon oxides, sulfur oxides, nitrogen oxides and crystalline silica.

SECTION 11: TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

Eye Effects: Causes moderate but temporary irritation

Skin Effects: LD50 is not determined. Prolonged exposure may cause mild irritation and dermatitis.

Acute Inhalation Effects: LC50 is not determined; Inhalation may cause respiratory tract irritation.

LD50 is not determined; Ingestion may cause severe irritation of the mouth throat and stomach. It Acute Oral Effects:

may also cause nausea, vomiting, and diarrhea

Specific Target Organ

Toxicity:

None known.

CHRONIC TOXICITY

Chronic Effects: Not anticipated to have chronic health effects due to exposure.

Carcinogenicity: None of the components of this product are known or suspected of having carcinogenic effects. Mutagenicity: None of the components of this product are known or suspected of having mutagenic effects. Teratogenicity: None of the components of this product are known or suspected of having teratogenic effects. Reproductive Toxicity: None of the components of this product are known or suspected of having effects on the

reproductive system.

Continued on Next Page

POTENTIAL HEALTH EFFECTS:

Eyes: Causes moderate but temporary irritation to the eyes.

Skin: Prolonged or repeated exposure may cause mild skin irritation. **Inhalation:** May be harmful if inhaled causing respiratory irritation.

Ingestion: May be harmful if swallowed.

SECTION 12: ECOLOGICAL INFORMATION

ENVIRONMENTAL SUMMARY: Not determined

ECOTOXICITY DATA:

Fish Acute and Prolonged Toxicity:

Aquatic Invertebrate Acute Toxicity:

Aquatic Plant Toxicity:

Bird Acute and Prolonged Toxicity:

Honeybee Toxicity:

Not determined

Not determined

Not determined

Not determined

ENVIRONMENTAL EFFECTS:

Soil Absorption/Mobility: Not determined Persistence and degradability: Not determined Bioaccumulative Potential: Not determined Other adverse effects: None known

SECTION 13: DISPOSAL CONSIDERATIONS

Waste: Dispose of in accordance with applicable Federal, state and local laws and regulations.

Container: Triple rinse and recycle the container or dispose of in accordance with Federal, state and local laws and regulations. **RCRA Characteristics:** It is the responsibility of the individual disposing of this product to determine the RCRA classification and hazard status of the waste.

SECTION 14: TRANSPORT INFORMATION		
DOT: (Ground)	Not regulated by the U.S. Department of Transportation as a hazardous substance.	
IMDG: (Sea)	Not determined	
IATA: (Air)	Not determined	
TDG: (Canada)	Not determined	

SECTION 15: REGULATORY INFORMATION

TSCA Inventory: All components are listed on the TSCA inventory or are exempt from listing.

SARA Title III Information:

Section 302 - Extremely hazardous substances: None listed

Section 311/312 – Hazard Categories: None listed

Section 313 – The following chemicals are subject to the reporting requirements of Section 313 of Title III, Superfund Amendments and Reauthorization Act of 1986 and 40 CFR 372:

None listed

CERCLA - This product contains the following chemicals which have a reportable quantity (RQ) under the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA):

None listed

California Proposition 65: This product does not contain any chemicals known to the state of California to cause cancer, birth defects or other reproductive harm.

Continued on next page

Foaminator® Dry

U.S. State Worker and Community Right-To-Know (RTK) Information (CT, IL, MA, MN, NH, NJ, PA, RI):

Chemical Name CAS # State(s)

None listed

Canadian Domestic Substances List: All components are listed.

WHMIS Classification: D2B

Other Information: A maximum of 1 ppm Ethylene Oxide (CAS # 75-21-8) may be present in this product. The OSHA PEL and the ACGIH TLV for Ethylene Oxide are 1 ppm. Ethylene Oxide is a NTP, IARC, and OSHA carcinogen. Ethylene Oxide has also been determined to be a reproductive hazard. The trace levels of Ethylene Oxide in this product are not expected to result in acute or long-term hazards when handled according to the precautions set forth in this SDS. However, Ethylene Oxide may accumulate in the container headspace and be released into the ambient environment. It is the responsibility of the employer to comply with OSHA Ethylene Oxide standards (29 CFR 1910.1047).

SECTION 16: OTHER

Disclaimer: The information presented herein is based on available data from reliable sources and is correct to the best of WinField Solutions' knowledge. WinField Solutions, LLC makes no warranty, express nor implied, regarding the accuracy of the data or the results obtained from the use of this product. Nothing herein may be construed as recommending any practice or any product in violation of any law or regulations. The user is solely responsible for determining the suitability of any material or product for a specific purpose and for adopting any appropriate safety precautions. We disclaim all liability for injury or damage stemming from any improper use of the material or product described herein.

Revision Date: April 23, 2014 Supersedes document dated: September 19, 2007

Sections Revised: All