

COBALT POWER™

Guaranteed Analysis

0-0-0

Cobalt (Co) 5.0%
5.0% Chelated Cobalt

Derived from cobalt sulfate, chelated with ethanol, 2-amino-2-hydroxy-1,2,3-propanetricarboxylate.

CAUTION

Keep out of Reach of Children • May Cause Eye Irritation

USER SAFETY RECOMMENDATIONS

Avoid contact with skin, eyes or clothing. Users should wash hands before eating, drinking, chewing gum, using tobacco or using the toilet. Remove wet clothing immediately. Wash skin thoroughly and put on clean clothing.

FIRST AID

Call a poison control center or doctor for treatment advice. Have product container or label with you when calling a poison control center, or doctor, or going for treatment. If in eyes: Hold eyes open and rinse slowly and gently with water for 15 to 20 minutes. If on skin: Take off contaminated clothing and rinse skin immediately with plenty of water for 15 to 20 minutes.

ENVIRONMENTAL HAZARDS

Do not apply directly to water, to areas where surface water is present, or to intertidal areas below the mean high water mark. Do not contaminate water when disposing of equipment wash water.

STORAGE AND DISPOSAL

Store this product out of direct sunlight, in a cool place above 40°F. Do not contaminate water, food or feed by storage or disposal. Do not reuse empty container. Dispose of empty container in a sanitary landfill or, if allowed by state and local authorities by burning. If burned, stay out of smoke.

COMPATIBILITY: Cobalt Power is tank-mix compatible with most pesticides and fertilizers. Add Cobalt Power to the diluted solution last. Always conduct a compatibility test for new or untried tank-mix combinations.

Information regarding the contents and levels of metals in this product is available on the internet at <http://www.aapco.org/metals>.

NET CONTENTS:

Net Weight: 10.35 lbs/gallon at 68°F

□ 2.5 gal. (25.88 lb) □ 55 gal. (569.25 lb) □ 10 liter (12.4 kg) □ 208 liter (257.92 kg)
□ 5.0 gal. (51.76 lb) □ 275 gal. (2846.25 lb) □ 20 liter (24.8 kg) □ 1040 liter (1289.6 kg)

COBALT POWER™

F001601



Z-COBALTP

Manufactured by Stoller Enterprises, Inc.
4001 W. Sam Houston Parkway North, Suite 100 | Houston Texas 77043 USA
Phone: 1-800-539-5283 or 713-461-1493 | Fax: 713-461-4467

GENERAL INFORMATION

Cobalt Power contains chelated complexes of plant available cobalt. Apply Cobalt Power to the soil or crop foliage for uptake by the plant. Use Cobalt Power before planting or early in plant development to avoid micronutrient deficiencies during growth.

DIRECTIONS FOR USE

It may be in violation of state law to use this product inconsistent with its labeling; always read and follow the label when using this product.

Use supplemental applications of cobalt when soil or foliage test results show limited amounts of other micronutrients or when other plant micronutrient deficiencies become evident. Cobalt Power can be applied as a pre-plant broadcast, in-furrow, as a side-dress or foliar application, and through flood, drip, overhead, pivot and micro irrigation systems. The addition of ammonium sulfate (or equivalent) at 0.5% v/v will increase uptake of Cobalt Power.

RECOMMENDED USES

Use Cobalt Power on the following Field Crops: alfalfa, asparagus, bean crops, canola, clover, corn, cotton, cruciferous crops, cucurbits, melons, milo, onion/garlic, peanut, pepper, potato, rape (canola), rice, soybean, sugar beet, sugarcane, sunflower, tobacco, tomato, vegetable crops, wheat/barley/oat; or Fruit and Nut Crops: almond, apple, apricot, avocado, banana, berry crops, cherry, citrus, coffee, fig, filbert, grapes, hazelnut, oil palm, olive, persimmon, peach, pear, pecan, pistachio, plums/prunes, pomegranate, strawberry and walnut.

FOR SOIL APPLICATION

Use Cobalt Power from 1 to 4 pints per acre.

FOR FOLIAR APPLICATION

Apply Cobalt Power at 1 pint per acre on actively growing crops in a minimum of 20 gallons of water per acre using split applications when appropriate.

HIGH VOLUME DRENCH: Apply 4 pints of Cobalt Power in 500 gallons of water.

LOW VOLUME EQUIPMENT: Apply 1 to 4 pints of Cobalt Power in 5 gallons of water per acre. Ariel applicators are not to exceed 2 pints of Cobalt Power per gallon of total solution volume.

Notice: The information contained herein is true and accurate to the best of our knowledge and belief, but is presented without guarantee since field conditions and use are beyond our control. Neither the manufacturer nor the seller make any warranty, expressed or implied, concerning the use of this product other than indicated on the label. Buyer assumes all risk of use of this material when such use is contrary to label instruction. Read and follow the label directions carefully. **CONDITIONS OF SALE:** 1. Seller warrants that this product consists of the ingredients specified and is reasonably fit for the purpose stated on this label when used in accordance with directions under normal conditions of use. No one, other than an officer of Seller, is authorized to make any warranty, guarantee of direction concerning this product. 2. Because of time, place, rate of application and other conditions of use are beyond sellers control, Sellers liability from handling, storage and use of this product is limited to replacement of product or refund of purchase price.