

Revision date: 2014/09/24 Page: 1/10 Version: 2.0 (30587274/SDS GEN US/EN)

## 1. Identification

Product identifier used on the label

## **CUSTOM SEED GLOSS 661**

#### Recommended use of the chemical and restriction on use

Recommended use\*: colouring component

## Details of the supplier of the safety data sheet

Company: BASF SE 67056 Ludwigshafen GERMANY Contact address:
BASF CORPORATION
100 Park Avenue
Florham Park, NJ 07932

USA

Telephone: +1 973 245-6000

## **Emergency telephone number**

CHEMTREC: 1-800-424-9300

BASF HOTLINE: 1-800-832-HELP (4357)

Other means of identification

## 2. Hazards Identification

## According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

## Classification of the product

No need for classification according to GHS criteria for this product.

#### Label elements

The product does not require a hazard warning label in accordance with GHS criteria.

## Hazards not otherwise classified

<sup>\*</sup> The "Recommended use" identified for this product is provided solely to comply with a US Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Revision date: 2014/09/24 Page: 2/10 Version: 2.0 (30587274/SDS\_GEN\_US/EN)

## Labeling of special preparations (GHS):

The following percentage of the mixture consists of components(s) with unknown hazards regarding the acute toxicity: 26 % dermal

The following percentage of the mixture consists of components(s) with unknown hazards regarding the acute toxicity: 21 % oral

The following percentage of the mixture consists of components(s) with unknown hazards regarding the acute toxicity: 26 % Inhalation - vapour

The following percentage of the mixture consists of components(s) with unknown hazards regarding the acute toxicity: 26 % Inhalation - mist

## According to Regulation 1994 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

## **Emergency overview**

Prolonged or repeated contact may cause mild eye irritation.

Prolonged or repeated contact may cause mild skin irritation.

Harmful if inhaled.

This product can contain a small amount of free respirable Crystalline (quartz) Silica which has been listed as a human carcinogen by NTP (Group 1) and IARC (Reasonably Anticipated to be a Human Carcinogen) and a Suspected Human Carcinogen by ACGIH (category A2).

Ingestion may cause gastrointestinal disturbances.

# 3. Composition / Information on Ingredients

#### According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

CAS Number	Content (W/W)	Chemical name
12001-26-2	15.0 - 30.0 %	Mica-group minerals
13463-67-7	5.0 - 15.0 %	Titanium dioxide
14808-60-7	0.1 - 1.0 %	crystalline silica

#### According to Regulation 1994 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

CAS Number	Content (W/W)	Chemical name
12001-26-2	15.0 - 30.0 %	Mica-group minerals
13463-67-7	5.0 - 15.0 %	Titanium dioxide
14808-60-7	0.1 - 1.0 %	crystalline silica
	55.0 - 80.0 %	Proprietary ingredients

## 4. First-Aid Measures

## **Description of first aid measures**

## **General advice:**

Remove contaminated clothing.

#### If inhaled:

Keep patient calm, remove to fresh air, seek medical attention.

## If on skin:

Wash thoroughly with soap and water.

#### If in eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open.

Revision date: 2014/09/24 Page: 3/10 Version: 2.0 (30587274/SDS GEN US/EN)

#### If swallowed:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

## Most important symptoms and effects, both acute and delayed

Symptoms: No significant reaction of the human body to the product known.

## Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment:

Treat according to symptoms (decontamination, vital functions), no known specific antidote.

## 5. Fire-Fighting Measures

## **Extinguishing media**

Suitable extinguishing media: water spray, dry powder, foam, carbon dioxide

## Special hazards arising from the substance or mixture

Hazards during fire-fighting:

carbon monoxide, carbon dioxide, nitrogen oxides

The substances/groups of substances mentioned can be released in case of fire.

#### Advice for fire-fighters

Protective equipment for fire-fighting:

Wear self-contained breathing apparatus and chemical-protective clothing.

#### Further information:

Keep containers cool by spraying with water if exposed to fire. In case of fire and/or explosion do not breathe fumes. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

#### 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

Do not breathe vapour/spray. Use personal protective clothing. Avoid contact with the skin, eyes and clothing.

## **Environmental precautions**

Do not discharge into the subsoil/soil. Do not discharge into drains/surface waters/groundwater.

#### Methods and material for containment and cleaning up

For small amounts: Pick up with suitable absorbent material (e.g. sand, sawdust, general-purpose binder, kieselguhr).

For large amounts: Dike spillage. Pump off product.

Dispose of absorbed material in accordance with regulations. Collect waste in suitable containers, which can be labeled and sealed. Clean contaminated floors and objects thoroughly with water and detergents, observing environmental regulations.

Revision date : 2014/09/24 Page: 4/10 Version: 2.0 (30587274/SDS\_GEN\_US/EN)

## 7. Handling and Storage

## Precautions for safe handling

No special measures necessary if stored and handled correctly. Ensure thorough ventilation of stores and work areas. When using do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift.

Protection against fire and explosion:

No special precautions necessary. The substance/product is non-combustible. Product is not explosive.

## Conditions for safe storage, including any incompatibilities

Segregate from foods and animal feeds.

Further information on storage conditions: Keep away from heat. Protect from direct sunlight.

# 8. Exposure Controls/Personal Protection

Components with occupational exposure limits				
crystalline silica	OSHA PEL	TWA value 2.4 millions of particles per cubic foot of air Respirable; The exposure limit is calculated from the equation, 250/(%SiO2+5), using a value of 100% SiO2. Lower percentages of SiO2 will yield higher exposure limits. TWA value 0.1 mg/m3 Respirable; The exposure limit is calculated from the equation, 10/(%SiO2+2), using a value of 100% SiO2. Lower percentages of SiO2 will yield higher exposure limits. TWA value 0.3 mg/m3 Total dust; The exposure limit is calculated from the equation, 30/(%SiO2+2), using a value of 100% SiO2. Lower percentages of SiO2 will yield higher exposure limits.		
	ACGIH TLV	TWA value 0.025 mg/m3 Respirable fraction;		
Titanium dioxide	OSHA PEL	PEL 15 mg/m3 Total dust ; TWA value 10 mg/m3 Total dust ; TWA value 10 mg/m3 ;		
	ACGIH TLV			
Mica-group minerals	OSHA PEL	TWA value 20 millions of particles per cubic foot of air; TWA value 3 mg/m3 Respirable dust; TWA value 20 millions of particles per cubic foot of air;		
	ACGIH TLV	TWA value 3 mg/m3 Respirable fraction;		

## Advice on system design:

Whenever possible, engineering controls should be used to minimize the need for personal protective equipment.

Revision date: 2014/09/24 Page: 5/10 Version: 2.0 (30587274/SDS\_GEN\_US/EN)

## Personal protective equipment

#### Respiratory protection:

Wear respiratory protection if ventilation is inadequate. Wear a NIOSH-certified (or equivalent) TC23C Chemical/Mechanical type filter system to remove a combination of particles, gas and vapours. For situations where the airborne concentrations may exceed the level for which an air purifying respirator is effective, or where the levels are unknown or Immediately Dangerous to Life or Health (IDLH), use NIOSH-certified full facepiece pressure demand self-contained breathing apparatus (SCBA) or a full facepiece pressure demand supplied-air respirator (SAR) with escape provisions.

## Hand protection:

Chemical resistant protective gloves, Protective glove selection must be based on the user's assessment of the workplace hazards.

#### Eve protection:

Safety glasses with side-shields. Tightly fitting safety goggles (chemical goggles). Wear face shield if splashing hazard exists.

#### **Body protection:**

Body protection must be chosen depending on activity and possible exposure, e.g. head protection, apron, protective boots, chemical-protection suit.

## General safety and hygiene measures:

Handle in accordance with good industrial hygiene and safety practice. Wearing of closed work clothing is recommended. Store work clothing separately. Keep away from food, drink and animal feeding stuffs.

# 9. Physical and Chemical Properties

Form: liquid Odour: faint odour

Odour threshold: Not determined due to potential health

hazard by inhalation.

Colour: off-white with pearly reflection pH value: approx. 8 - 9.5 ( 20 °C)

Melting temperature: approx. 0 °C Information applies to the solvent. boiling temperature: approx. 100 °C Information applies to the solvent.

Flash point: > 100 °C not applicable

Lower explosion limit: As a result of our experience with this

product and our knowledge of its

composition we do not expect any hazard

as long as the product is used

appropriately and in accordance with the

intended use.

Upper explosion limit: As a result of our experience with this

product and our knowledge of its

composition we do not expect any hazard

as long as the product is used

appropriately and in accordance with the

intended use.

Autoignition: Based on the water content the product

does not ignite.

Vapour pressure: approx. 23.4 hPa (20 °C) Information applies to the

solvent.

Density: approx. 1.2 (20 °C)

g/cm3

Revision date : 2014/09/24 Page: 6/10 Version: 2.0 (30587274/SDS\_GEN\_US/EN)

Vapour density: not applicable Partitioning coefficient n- not applicable

octanol/water (log Pow):

Thermal decomposition: No decomposition if stored and handled as

prescribed/indicated.

Viscosity, kinematic: Forms a viscous solution.

Solubility in water: dispersible Evaporation rate: not applicable

Other Information: If necessary, information on other physical and chemical

parameters is indicated in this section.

# 10. Stability and Reactivity

## Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Oxidizing properties:

Based on its structural properties the product is not classified as oxidizing.

## **Chemical stability**

The product is stable if stored and handled as prescribed/indicated.

## Possibility of hazardous reactions

No hazardous reactions if stored and handled as prescribed/indicated.

#### Conditions to avoid

See MSDS section 7 - Handling and storage.

#### Incompatible materials

strong acids, strong bases, strong oxidizing agents

## **Hazardous decomposition products**

Decomposition products:

Hazardous decomposition products: No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:

No decomposition if stored and handled as prescribed/indicated.

## 11. Toxicological information

#### Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

## **Acute Toxicity/Effects**

### Acute toxicity

Assessment of acute toxicity: Virtually nontoxic after a single ingestion. Virtually nontoxic by inhalation. Virtually nontoxic after a single skin contact.

## Oral

Type of value: ATE

Revision date : 2014/09/24 Page: 7/10 Version: 2.0 (30587274/SDS\_GEN\_US/EN)

Value: > 5,000 mg/kg

**Inhalation** 

Type of value: ATE Value: > 20.0000 mg/l Determined for vapor

Type of value: ATE Value: > 5.0000 mg/l Determined for mist

Dermal

Type of value: ATE Value: > 5,000 mg/kg

Irritation / corrosion

Assessment of irritating effects: Not irritating to the skin. Not irritating to the eyes.

Sensitization

Assessment of sensitization: There is no evidence of a skin-sensitizing potential.

## **Chronic Toxicity/Effects**

### Repeated dose toxicity

Assessment of repeated dose toxicity: The product has not been tested. The statement has been derived from the properties of the individual components.

Information on: crystalline silica

Assessment of repeated dose toxicity: The substance may cause increase in lung mass and lung tissue changes after repeated inhalation.

This product may contain greater than 0.1% crystalline silica. Repeated exposure to high concentrations results in silicosis, a lung disease characterized by coughing, difficult breathing, wheezing, scarring of the lungs, and repeated, non-specific chest illnesses.

.....

#### **Genetic toxicity**

Assessment of mutagenicity: The product has not been tested. The statement has been derived from the properties of the individual components. Mutagenicity tests revealed no genotoxic potential.

### Carcinogenicity

Assessment of carcinogenicity: The product has not been tested. The statement has been derived from the properties of the individual components.

Information on: Titanium dioxide

Assessment of carcinogenicity: IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans). In long-term studies in rats in which the substance was given by inhalation, a carcinogenic effect was observed. Tumors were only observed in rats after chronic inhalative exposure to high concentrations which caused sustained lung inflammation. In long-term studies in rats and mice in which the substance was given by feed, a carcinogenic effect was not observed. Dermal exposure is not expected to be carcinogenic.

-----

Information on: crystalline silica

Assessment of carcinogenicity: In long-term studies in rats and mice in which the substance was given by feed, a carcinogenic effect was not observed. In long-term animal studies in which the

Revision date : 2014/09/24 Page: 8/10 Version: 2.0 (30587274/SDS\_GEN\_US/EN)

substance was given by inhalation in high doses, a carcinogenic effect was observed. The substance and its compounds in the form of respirable dusts/aerosolsis classified by the German MAK commision as a category 1 carcinogen (substances that cause cancer to humans). A carcinogenic effect cannot safely be ruled out. The inhalation uptake of the alveolar fraction of the fine dust may cause damage to the lungs. The International Agency for Research on Cancer (IARC) has classified this substance as a Group 1 (known) human carcinogen.

The International Agency for Research on Cancer (IARC) has classified this substance as a Group 1 (known) human carcinogen.

NTP listed carcinogen

\_\_\_\_\_

#### Reproductive toxicity

Assessment of reproduction toxicity: The product has not been tested. The statement has been derived from the properties of the individual components. The results of animal studies gave no indication of a fertility impairing effect.

#### **Teratogenicity**

Assessment of teratogenicity: The product has not been tested. The statement has been derived from the properties of the individual components. Animal studies gave no indication of a developmental toxic effect at doses that were not toxic to the parental animals.

#### Other Information

Misuse can be harmful to health.

## Symptoms of Exposure

No significant reaction of the human body to the product known.

## 12. Ecological Information

## **Toxicity**

Aquatic toxicity

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms.

Toxicity to fish

No data available.

Aquatic invertebrates

No data available.

Aquatic plants

No data available.

## Persistence and degradability

## Assessment biodegradation and elimination (H2O)

The product has not been tested. The statement has been derived from the properties of the individual components. Colourants are by their nature very stable and are therefore not readily biodegradable under conditions prevailing in surface water or in effluent treatment plants.

## Bioaccumulative potential

Assessment bioaccumulation potential

Revision date: 2014/09/24 Page: 9/10 Version: 2.0 (30587274/SDS\_GEN\_US/EN)

The product has not been tested.

#### Bioaccumulation potential

Significant accumulation in organisms is not to be expected.

## Mobility in soil

## Assessment transport between environmental compartments

Adsorption to solid soil phase is expected.

The product has not been tested. The statement has been derived from the properties of the individual components.

#### Additional information

Other ecotoxicological advice:

Do not discharge product into the environment without control.

# 13. Disposal considerations

### Waste disposal of substance:

Must be disposed of or incinerated in accordance with local regulations.

### Container disposal:

Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

## 14. Transport Information

## **Land transport**

**USDOT** 

Not classified as a dangerous good under transport regulations

#### Sea transport

**IMDG** 

Not classified as a dangerous good under transport regulations

### Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

# 15. Regulatory Information

## **Federal Regulations**

#### Registration status:

Chemical TSCA, US released / listed

EPCRA 311/312 (Hazard categories): Acute; Chronic

## State regulations

Revision date: 2014/09/24 Page: 10/10 Version: 2.0 (30587274/SDS\_GEN\_US/EN)

State RTKCAS NumberChemical nameMA, NJ, PA12001-26-2Mica-group mineralsMA, NJ, PA13463-67-7Titanium dioxideMA, NJ, PA14808-60-7crystalline silica

CA Prop. 65:

WARNING: THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF

CALIFORNIA TO CAUSE CANCER.

## 16. Other Information

#### SDS Prepared by:

BASF NA Product Regulations SDS Prepared on: 2014/09/24

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

**END OF DATA SHEET**