

The Andersons Professional Turf™ Products 30-0-10

- Contains proprietary NS-54™ coated slow release nitrogen to provide uniform growth with extended nitrogen feeding.
- Provides quick initial green-up from urea nitrogen.

GUARANTEED ANALYSIS

| | |
|---|--------|
| Total Nitrogen (N) | 30.00% |
| 30.00% Urea Nitrogen* | |
| Soluble Potash (K ₂ O) | 10.00% |
| Sulfur (S) | 1.10% |
| 1.10% Free Sulfur (S) | |

Plant nutrients derived from urea, potassium chloride and polymer coated sulfur coated urea.
Chlorine (Cl) Max

8.46%

*12.00% Slowly available nitrogen from polymer coated sulfur coated urea.

F002091

Information regarding the contents and levels of metals in this product is available on the internet at <http://www.regulatory-info-ap.com>

GENERAL INFORMATION

The Andersons Professional Turf™ Products 30-0-10 provides grass with nitrogen, and potash for maintaining strong, vigorous turf.

The nitrogen in this product is both readily and slowly available which makes this product excellent for applications throughout the growing season when the minimum soil temperatures are greater than 55°F to 60°F and not exceeding 85°F.

This product is dust free and free flowing. The uniform particle sizing assures easy and accurate applications.

Do not apply near water, storm drains or drainage ditches. Do not apply if heavy rain is expected. Apply this product only to your lawn and sweep any product that lands on the driveway, sidewalk or street, back onto your lawn.

WHEN AND HOW TO USE

In the spring, or as soon as weather and ground conditions permit, apply 1.65 to 5.00 pounds of this product per 1,000 square feet. Repeat every six to eight weeks throughout the growing season.

To ensure that you have the best possible fertilization program, use fertilizers in conjunction with a soil and tissue test program operated by a state certified laboratory familiar with the soils of your region. Cooperative extension agents can provide the names of recommended labs in your area.

Apply only as directed.

IMPORTANT: READ BEFORE USE:

Read the entire Directions for Use and the Warranty Disclaimer and Limitation of Liability before using this product. If terms are not acceptable, return the unopened product container at once. By using this product, user or Buyer accepts the following Warranty Disclaimer and Limitation of Liability:

WARRANTY DISCLAIMER and LIMITATION of LIABILITY:

Manufacturer warrants that this product conforms to the chemical description on the label and is reasonably fit for the purposes stated on the label when used in strict accordance with the directions. Manufacturer makes NO OTHER EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

To the extent consistent with applicable law, it is Manufacturer's intent to LIMIT ANY LIABILITY FOR SPECIAL, CONSEQUENTIAL OR INCIDENTAL ECONOMIC DAMAGES to refund of purchase price or replacement of product, at Buyer's choice. To the extent consistent with applicable law, Manufacturer DISCLAIMS ANY LIABILITY FOR COMPENSATORY OR OTHER DAMAGES ARISING OUT OF ANY USE CONTRARY TO LABEL DIRECTIONS.

LEGAL RIGHTS:

THIS LIMITED WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS; YOU MAY HAVE OTHER RIGHTS THAT VARY FROM STATE/JURISDICTION TO STATE/JURISDICTION.

Product of U.S.A.

Manufactured by:
The Andersons, Inc.
P.O. Box 119
Maumee, OH 43537
www.andersonsplantnutrient.com

Professional Turf and NS-54 are trademarks of The Andersons, Inc.

| Suggested Spreader Settings | | | | | |
|---|--------------|-------------------|------------------------------------|---------------------------------------|-------------------------------------|
| <i>These suggested spreader settings are not intended to replace calibration. Please calibrate your spreader before applying product.</i> | | | | | |
| 50 lbs. feeds 30,300 sq. ft. (0.70 acre) with 0.50 lbs. N/1,000 sq. ft. at the LOW RATE | | | | | |
| 50 lbs. feeds 15,000 sq. ft. (0.34 acre) with 1.00 lbs. N/1,000 sq. ft. at the MEDIUM RATE | | | | | |
| 50 lbs. feeds 10,000 sq. ft. (0.23 acre) with 1.50 lbs. N/1000 sq. ft. at the HIGH RATE | | | | | |
| SPREADER | GROUND SPEED | WIDTH OF COVERAGE | SPREADER SETTINGS | | |
| | | | LOW RATE 1.65 lbs/1,000 sq. ft. | MEDIUM RATE 3.33 lbs/1,000 sq. ft. | HIGH RATE 5.00 lbs/1,000 sq. ft. |
| Andersons Model 2000 / AccuPro 2000 (cone 4); Andersons 2000 SR / SR-2000 (cone 4) | 3 mph | 11 feet | J 3/4 | L 1/4 | N 1/2 |
| Scotts R-8A (cone 4) | 3 mph | 11 feet | I 1/2 | K 1/4 | M 3/4 |
| Lesco 020093 (pattern 0.25) | 3 mph | 10 feet | D | F | G 1/2 |
| Lesco 705698 (pattern 0.25) | 3 mph | 10 feet | 10 | 14 | 17 |
| Lely Models WTR, WFR, HR, 1250 (PTO at 450 rpm) Pattern I | 4.5 mph | 40 feet | 4 1/2 | 5 3/4 | 7 |
| Vicon (03 Series) | 4.5 mph | 36 feet | 21 | 27 | 35 |

Net Wt. 50 Lbs. (22.68 kg)



APT30125.40