

The Andersons

Professional Turf™ Products

32-3-10 with PCSCU

- Contains proprietary NS-54™ coated slow release nitrogen to provide uniform growth with extended nitrogen feeding
- Free flowing, non-dusty formula

Guaranteed Analysis

Total Nitrogen (N)	32.00%
1.17% Ammoniacal Nitrogen	
30.83% Urea Nitrogen*	
Available Phosphate (P ₂ O ₅)	3.00%
Soluble Potash (K ₂ O)	10.00%

Plant nutrients derived from diammonium phosphate, urea, potassium chloride and polymer coated sulfur coated urea.

Chlorine (Cl) Max	8.45%
-----------------------------	-------

*6.40% Slowly available urea nitrogen from polymer coated sulfur coated urea.

F002091

DIRECTIONS FOR USE

Apply only as directed. Apply during the growing season.

Application Rates:

LOW:	1.55 lbs/1,000 sq. ft.
MEDIUM:	3.15 lbs/1,000 sq. ft.
HIGH:	4.70 lbs/1,000 sq. ft.

For all applications:

- Apply to dry foliage.
- Water in after application with a minimum of 0.2 inches to help move particles into the turf canopy.
- Do not collect clippings for at least one mowing following application to avoid particle pick-up.

Cool Season Grasses:

- Apply at the MEDIUM RATE.
- Apply at the LOW RATE when temperatures exceed 85°F.

Warm Season Grasses:

- Apply at the MEDIUM or HIGH RATE every 4-6 weeks during the period of active growth.

Do not apply near water, storm drains or drainage ditches. Do not apply if heavy rain is expected. Apply this product only to your lawn and sweep any product that lands on the driveway, sidewalk or street, back onto your lawn.

STORAGE AND USE

Store in a clean, dry place.
Reseal opened bag by folding top down and securing.
Use only in clean, dry spreaders.
Do not leave unused product in spreaders.

IMPORTANT: READ BEFORE USE:

Read the entire Directions for Use and the Warranty Disclaimer and Limitation of Liability before using this product. If terms are not acceptable, return the unopened product container at once. By using this product, user or Buyer accepts the following Warranty Disclaimer and Limitation of Liability:

WARRANTY DISCLAIMER and LIMITATION of LIABILITY:

Manufacturer warrants that this product conforms to the chemical description on the label and is reasonably fit for the purposes stated on the label when used in strict accordance with the directions. Manufacturer makes NO OTHER EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS

FOR A PARTICULAR PURPOSE. To the extent consistent with applicable law, it is Manufacturer's intent to LIMIT ANY LIABILITY FOR SPECIAL, CONSEQUENTIAL OR INCIDENTAL ECONOMIC DAMAGES to refund of purchase price or replacement of product, at Buyer's choice. To the extent consistent with applicable law, Manufacturer DISCLAIMS ANY LIABILITY FOR COMPENSATORY OR OTHER DAMAGES ARISING OUT OF ANY USE CONTRARY TO LABEL DIRECTIONS.

LEGAL RIGHTS:

THIS LIMITED WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS; YOU MAY HAVE OTHER RIGHTS THAT VARY FROM STATE/JURISDICTION TO STATE/JURISDICTION.

Product of USA

Manufactured by:
The Andersons, Inc.
P.O. Box 119
Maumee, OH 43537
www.andersonsplantnutrient.com

NS-54 is a trademark of The Andersons, Inc.

Suggested Spreader Settings These suggested spreader settings are not intended to replace calibration. Please calibrate your spreader prior to applying product. 50 lbs. feeds 32,200 sq. ft. (0.74 acre) with 0.496 lbs. N/1,000 sq. ft. at the LOW RATE 50 lbs. feeds 15,800 sq. ft. (0.36 acre) with 1.008 lbs. N/1,000 sq. ft. at the MEDIUM RATE 50 lbs. feeds 10,600 sq. ft. (0.24 acre) with 1.504 lbs. N/1,000 sq. ft. at the HIGH RATE					
SPREADER	GROUND SPEED	WIDTH OF COVERAGE	SPREADER SETTINGS		
			LOW RATE 1.55 lbs/1,000 sq. ft.	MEDIUM RATE 3.15 lbs/1,000 sq. ft.	HIGH RATE 4.70 lbs/1,000 sq. ft.
Andersons Model 2000 / AccuPro 2000 (cone 4); Andersons 2000 SR / SR-2000 (cone 4)	3 mph	10 feet	I 1/2	L 1/4	M 3/4
Andersons LCO-1000	3 mph	10 feet	I 1/2	L 1/4	M 3/4
Scotts R-8, R-8A (cone 4)	3 mph	10 feet	I	K 1/4	L 3/4
Lesco 020093 (pattern 0.25)	3 mph	7 feet	C 1/2	E	E 1/2
Lesco 705698 (pattern 0.25)	3 mph	7 feet	9	12	13
Lely Models WTR, WFR, HR, 1250 (PTO at 450 rpm) Pattern II-C	4.5 mph	34 feet	4 /12	5 1/2	6 3/4
Vicon (03 Series)	4.5 mph	28 feet	20	27	35

Net Wt. 50 Lbs. (22.68 kg)



APT32655.40