

Andersons Golf Products Turf Fertilizer 23-0-10

with Poly-S® Nitrogen & Iron

- Utilizes Poly-S® coated slow release nitrogen to provide uniform growth with extended nitrogen feeding
- Contains iron for improved turf color
- SGN 150 particle size for use on fairways & roughs

Guaranteed Analysis

Total Nitrogen (N)	23.00%
23.00% Urea Nitrogen*	
Soluble Potash (K ₂ O)	10.00%
Sulfur (S)	4.79%
1.39% Free Sulfur (S)	
3.40% Combined Sulfur (S)	
Iron (Fe)	5.00%

Plant nutrients derived from urea, potassium sulfate, polymer coated sulfur coated urea, and ferric sucrate.

*14.95% Slowly available urea nitrogen from polymer coated sulfur coated urea.

F002091

Information regarding the contents and levels of metals in this product is available on the internet at <http://www.regulatory-info-ap.com>

DIRECTIONS FOR USE

Apply only as directed. Apply during the growing season.

Application Rates:

LIGHT: 2.10 lbs/1,000 sq. ft.
MEDIUM: 4.30 lbs/1,000 sq. ft.

For all applications:

- Apply to dry foliage.
- Water in after application with a minimum of 0.2 inches to help move particles into the turf canopy.
- Do not collect clippings for at least one mowing following application to avoid particle pick-up.
- Apply at the LIGHT RATE when temperatures exceed 85°F.

Do not apply near water, storm drains or drainage ditches. Do not apply if heavy rain is expected. Apply this product only to your lawn and sweep any product that lands on the driveway, sidewalk or street, back onto your lawn.

Note: This product contains the micronutrient iron for extra greening and to help prevent iron deficiency. Iron may stain concrete and other surfaces. Misapplied product to these surfaces should be removed promptly by sweeping or blowing. DO NOT WASH OFF WITH WATER.

STORAGE AND USE

Store in a clean, dry place.
Reseal opened bag by folding top down and securing.
Use only clean, dry spreaders.
Do not leave unused product in spreaders.

IMPORTANT: READ BEFORE USE:

Read the entire Directions for Use and the Warranty Disclaimer and Limitation of Liability before using this product. If terms are not acceptable, return the unopened product container at once. By using this product, user or Buyer accepts the following Warranty Disclaimer and Limitation of Liability:

WARRANTY DISCLAIMER and LIMITATION of LIABILITY:

Manufacturer warrants that this product conforms to the chemical description on the label and is reasonably fit for the purposes stated on the label when used in strict accordance with the directions. Manufacturer makes NO OTHER EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. To the extent consistent with applicable law, it is Manufacturer's intent to LIMIT ANY LIABILITY FOR SPECIAL, CONSEQUENTIAL OR INCIDENTAL ECONOMIC DAMAGES to refund of purchase price or replacement of product, at Buyer's choice. To the extent consistent with applicable law, Manufacturer DISCLAIMS ANY LIABILITY FOR COMPENSATORY OR OTHER DAMAGES ARISING OUT OF ANY USE CONTRARY TO LABEL DIRECTIONS.

LEGAL RIGHTS:

THIS LIMITED WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS; YOU MAY HAVE OTHER RIGHTS THAT VARY FROM STATE/JURISDICTION TO STATE/JURISDICTION.

Product of U.S.A.

Manufactured by:
The Andersons, Inc.
P.O. Box 119
Maumee, OH 43537
www.andersonsplantnutrient.com

Poly-S is a registered trademark of The Scotts Co.

SUGGESTED SPREADER SETTINGS

These suggested spreader settings are not intended to replace calibration.

Please calibrate your spreader before applying product.

50 lbs. feeds 23,800 sq. ft. (0.55 acre) with 0.48 lbs. N/1,000 sq. ft. at the LIGHT RATE
50 lbs. covers 11,600 sq. ft. (0.27 acre) with 0.98 lbs. N/1,000 sq. ft. at the MEDIUM RATE

SPREADER	GROUND SPEED	WIDTH OF COVERAGE	LIGHT RATE 2.1 lbs/1,000 sq. ft.	MEDIUM RATE 4.3 lbs/1,000 sq. ft.
Andersons Model 2000 / AccuPro 2000 (cone 6); Andersons 2000 SR / SR-2000 (cone 6)	3 mph	12 feet	J 1/2	L 1/2
Scotts R-8, R-8A (cone 6)	3 mph	11 feet	H 1/2	J
Lesco 020093 (pattern 0.25)	3 mph	10 feet	E	G 1/2
Lesco 705698 (pattern 0.25)	3 mph	10 feet	12	17
Lely Models WTR, WFR, HR, 1250 (PTO at 450 rpm) Pattern I	4.5 mph	36 feet	4 1/2	6
Vicon (03 Series)	4.5 mph	30 feet	19	29

SGN 150

Net Wt. 50 Lbs. (22.68 kg)



AGC231FE50.40

J16*