

Sanitek Products, Inc.		Page: 1
SAFETY DATA SHEET		Revision Date: 09/07/2016
		Print Date: 8/3/2017
		SDS Number: 0000001
38-F DRIFT RETARDANT		Version: 1.50

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : 38 F DRIFT RETARDANT

Recommended use of the chemical and restrictions on use

<p>Details of the supplier of the safety data sheet SANAG (div of Sanitek Products, Inc.) 3959 Goodwin Ave. Los Angeles, CA 90039</p>	<p>Emergency telephone number CHEMTEL, INC. (1-800-255-3924)</p> <p>Product Information Sanitek (1-323-245-6781)</p>
---	--

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification


Skin irritation : Category 2


Eye irritation : Category 2A

Specific target organ systemic toxicity - single exposure : Category 3 (Central nervous system)

Aspiration hazard : Category 1

GHS label elements

Hazard pictograms : 

 Signal Word : Danger

Sanitek Products, Inc.		Page: 2
SAFETY DATA SHEET		Revision Date: 09/07/2016
		Print Date: 8/3/2017
		SDS Number: 0000001
38-F DRIFT RETARDANT		Version: 1.5

Hazard Statements : May be fatal if swallowed and enters airways.
 Causes skin irritation.
 Causes serious eye irritation.
 May cause drowsiness or dizziness.

Precautionary Statements : **Prevention:**
 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
 Wash skin thoroughly after handling.
 Use only outdoors or in a well-ventilated area.
 Wear eye protection/ face protection.
 Wear protective gloves.
 Wear respiratory protection.
Response:
 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
 IF ON SKIN: Wash with plenty of soap and water.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 Do NOT induce vomiting.
 If skin irritation occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention.
 Take off contaminated clothing and wash before reuse.
Storage:
 Store in a well-ventilated place. Keep container tightly closed.
 Store locked up.
Disposal:
 Dispose of contents/ container to an approved waste disposal plant.

Other hazards
 Static Accumulating liquid

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture
 Chemical nature : Static Accumulator
 Chemical nature : Defatter

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
---------------	---------	----------------	-------------------

Sanitek Products, Inc.		Page: 3
SAFETY DATA SHEET		Revision Date: 09/07/2016
		Print Date: 8/3/2017
		SDS Number: 0000001
38-F DRIFT RETARDANT		Version: 1.5

ALIPHATIC HYDROCARBON	254504001-5164	Flam. Liq. 4; H227 Skin Irrit. 2; H315 STOT SE 3; H336	>= 20.00 - < 30.00
POLYMER	254504001-5817	Acute Tox. 4; H302 Eye Dam. 1; H318	>= 1.00 - < 1.50

Trade Secret Composition - conceal identity + concentration

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Call a POISON CENTRE or doctor/physician if exposed or you feel unwell.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.
- If inhaled : Move to fresh air.
If unconscious place in recovery position and seek medical advice.
Consult a physician after significant exposure.
- In case of skin contact : Remove contaminated clothing. If irritation develops, get medical attention.
If on skin, rinse well with water.
Wash contaminated clothing before re-use.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
- If swallowed : Obtain medical attention.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms : Inhalation of high concentrations of this material, as could

Sanitek Products, Inc.		Page: 4
SAFETY DATA SHEET		Revision Date: 09/07/2016
		Print Date: 8/3/2017
		SDS Number: 0000001
38-F DRIFT RETARDANT		Version: 1.5

and effects, both acute and delayed

occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material.

This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 2 - Swallowing) when deciding whether to induce vomiting.

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:

stomach or intestinal upset (nausea, vomiting, diarrhea)
irritation (nose, throat, airways)

Lung irritation

confusion

irregular heartbeat

Convulsions

May be fatal if swallowed and enters airways.

Causes skin irritation.

Causes serious eye irritation.

May cause drowsiness or dizziness.

Notes to physician

: No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Water spray

Foam

Carbon dioxide (CO₂)

Dry chemical

Unsuitable extinguishing media : High volume water jet

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : carbon dioxide and carbon monoxide
Nitrogen oxides (NO_x)
Hydrocarbons

Specific extinguishing methods :

Sanitek Products, Inc.		Page: 5
SAFETY DATA SHEET		Revision Date: 09/07/2016
		Print Date: 8/3/2017
		SDS Number: 0000001
38-F DRIFT RETARDANT		Version: 1.5

Product is compatible with standard fire-fighting agents.

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Avoid formation of aerosol.
Provide sufficient air exchange and/or exhaust in work rooms.
Do not breathe vapours/dust.
Do not smoke.
Container hazardous when empty.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Sanitek Products, Inc.		Page: 6
SAFETY DATA SHEET		Revision Date: 09/07/2016
		Print Date: 8/3/2017
		SDS Number: 0000001
38-F DRIFT RETARDANT		Version: 1.5

Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
ALIPHATIC HYDROCARBON	254504001-5164	TWA	200 mg/m ³ Non-aerosol (as total hydrocarbon vapor)	ACGIH
		REL	100 mg/m ³	NIOSH/GUID E

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

In the case of vapour formation use a respirator with an approved filter.

Hand protection
Remarks

: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Wear chemical splash goggles when there is the potential for

Sanitek Products, Inc.		Page: 7
SAFETY DATA SHEET		Revision Date: 09/07/2016
		Print Date: 8/3/2017
		SDS Number: 0000001
38-F DRIFT RETARDANT		Version: 1.5

exposure of the eyes to liquid, vapor or mist.

- Skin and body protection : Wear resistant gloves (consult your safety equipment supplier).
Wear as appropriate:
Impervious clothing
Safety shoes
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Discard gloves that show tears, pinholes, or signs of wear.
- Hygiene measures : Wash hands before breaks and at the end of workday.
When using do not eat or drink.
When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : viscous
- Physical state : liquid
- Colour : white, milky
- Odour : mild, hydrocarbon-like
- Odour Threshold : No data available
- pH : 6 - 8
- Melting point/freezing point : 0 °F / -18 °C Boiling point/boiling range : No data available Flash point : > 200.1 °F / > 93.4 °C Evaporation rate : < 1
- Flammability (solid, gas) :
No data available
- Flammability (liquids) : Static Accumulating liquid
- Flammability (liquids)
Upper explosion limit : No data available

Sanitek Products, Inc.		Page: 8
SAFETY DATA SHEET		Revision Date: 09/07/2016
		Print Date: 8/3/2017
		SDS Number: 0000001
38-F DRIFT RETARDANT		Version: 1.5

Lower explosion limit : No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : Approximate 1

Density : Approximate 1.05 g/cm3

Solubility(ies)
Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-
octanol/water : No data available

Thermal decomposition : No data available

Viscosity
Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Product will not undergo hazardous polymerization.

Conditions to avoid : Heat, flames and sparks.
Exposure to sunlight.
Exposure to moisture

Incompatible materials : Acids
halogenated hydrocarbons
Metals
organic nitro compounds
oxidizers
Strong bases

Sanitek Products, Inc.		Page: 9
SAFETY DATA SHEET		Revision Date: 09/07/2016
		Print Date: 8/3/2017
		SDS Number: 0000001
38-F DRIFT RETARDANT		Version: 1.5

Strong oxidizing agents
strong reducing agents
water

Hazardous decomposition
products

carbon dioxide and carbon monoxide
Hydrocarbons

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Components:

ALIPHATIC HYDROCARBON:

Acute oral toxicity : LD 50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC 50 (Rat, male and female): > 5.28 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD 50 (Rabbit): > 2,000 mg/kg
Assessment: No adverse effect has been observed in acute dermal toxicity tests.

POLYMER:

Acute oral toxicity :
Assessment: The component/mixture is classified as acute oral toxicity, category 4.

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks: May cause skin irritation and/or dermatitis.

Result: Repeated exposure may cause skin dryness or cracking.

Sanitek Products, Inc.		Page: 10
SAFETY DATA SHEET		Revision Date: 09/07/2016
		Print Date: 8/3/2017
		SDS Number: 0000001
38-F DRIFT RETARDANT		Version: 1.5

Components:

ALIPHATIC HYDROCARBON:

Result: Mildly irritating to skin

POLYMER:

Result: Not irritating to skin

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin., Causes serious eye irritation.

Components:

ALIPHATIC HYDROCARBON:

Result: Mildly irritating to eyes

POLYMER:

Result: Corrosive to eyes

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.

Components:

ALIPHATIC HYDROCARBON:

Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Product:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

Sanitek Products, Inc.		Page: 11
SAFETY DATA SHEET		Revision Date: 09/07/2016
		Print Date: 8/3/2017
		SDS Number: 0000001
38-F DRIFT RETARDANT		Version: 1.5

Carcinogenicity:

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

- Toxicity to fish : LC 50 (Pimephales promelas (fathead minnow)): > 100 mg/l
 Exposure time: 96 h
 Test substance: Polymer
 Method: OECD Test Guideline 203
 Remarks: Test conducted using environmentally representative water.
- Toxicity to daphnia and other aquatic invertebrates : EC 50 (Water flea (Daphnia magna)): > 100 mg/l
 Exposure time: 48 h
 Test substance: Polymer
 Method: OECD Test Guideline 202
 Remarks: Test conducted using environmentally representative water.
- Toxicity to algae : IC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
 Exposure time: 72 h
 Test substance: Polymer
 Method: OECD Test Guideline 201
 Remarks: Test conducted using environmentally representative water.
- Ecotoxicology Assessment
 Acute aquatic toxicity : Not classified based on available information.
- Chronic aquatic toxicity : Chronic aquatic toxicity Category 2; Toxic to aquatic life with long lasting effects.

Sanitek Products, Inc.		Page: 12
SAFETY DATA SHEET		Revision Date: 09/07/2016
		Print Date: 8/3/2017
		SDS Number: 0000001
38-F DRIFT RETARDANT		Version: 1.5

Components:

ALIPHATIC HYDROCARBON:

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 - 5 mg/l
 Exposure time: 96 h
 Test Type: semi-static test
 Test substance: WAF
 Method: OECD Test Guideline 203
 Remarks: Information given is based on data obtained from similar substances.
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Water flea (Daphnia magna)): 1.4 mg/l
 Exposure time: 48 h
 Test Type: static test
 Test substance: WAF
 Method: OECD Test Guideline 202
 Remarks: Information given is based on data obtained from similar substances.
- Toxicity to algae : EL50 (Pseudokirchneriella subcapitata (green algae)): > 1 - 3 mg/l
 Exposure time: 72 h
 Test Type: static test
 Test substance: WAF
 Method: OECD Test Guideline 201
 Remarks: Information given is based on data obtained from similar substances.
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEL (Water flea (Daphnia magna)): 0.48 mg/l
 Exposure time: 21 d
 Test Type: semi-static test
 Test substance: WAF
 Method: OECD Test Guideline 211
 Remarks: Information given is based on data obtained from similar substances.

Persistence and degradability

Components:

ALIPHATIC HYDROCARBON:

- Biodegradability : Result: Inherently biodegradable.
 Biodegradation: 58.6 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301F

POLYMER:

- Biodegradability : Biodegradation: > 90 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301E

Sanitek Products, Inc.		Page: 13
SAFETY DATA SHEET		Revision Date: 09/07/2016
		Print Date: 8/3/2017
		SDS Number: 0000001
38-F DRIFT RETARDANT		Version: 1.5

Remarks: Information given is based on data obtained from similar substances.

Bioaccumulative potential

Components:

No data available

Mobility in soil

Components:

No data available

Other adverse effects

No data available

Product:

Additional ecological information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life with long lasting effects.

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice

: The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging

: Empty remaining contents.
Dispose of as unused product.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

Sanitek Products, Inc.		Page: 14
SAFETY DATA SHEET		Revision Date: 09/07/2016
		Print Date: 8/3/2017
		SDS Number: 0000001
38-F DRIFT RETARDANT		Version: 1.5

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	------------------------------

MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

TRANSPORT CANADA - INLAND WATERWAYS

Not dangerous goods

TRANSPORT CANADA - RAIL

Not dangerous goods

TRANSPORT CANADA - ROAD

Not dangerous goods	MARINE POLLUTANT:(HYDROTREA TED PETROLEUM DISTILLATES)
---------------------	---

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

U.S. DOT - RAIL

Not dangerous goods

U.S. DOT - ROAD

Sanitek Products, Inc.		Page: 15
SAFETY DATA SHEET		Revision Date: 09/07/2016
		Print Date: 8/3/2017
		SDS Number: 0000001
38-F DRIFT RETARDANT		Version: 1.5

Not dangerous goods

***ORM = ORM-D, CBL = COMBUSTIBLE LIQUID**

Marine pollutant	yes
------------------	-----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
SODIUM HYDROXIDE	1310-73-2	1000	25000

SARA 311/312 Hazards : Acute Health Hazard

SARA 313 Component(s)SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

The components of this product are reported in the following inventories:

- TSCA : On TSCA Inventory
- DSL : All components of this product are on the Canadian DSL
- AUSTR : On the inventory, or in compliance with the inventory
- ENCS : Not in compliance with the inventory
- KECL : On the inventory, or in compliance with the inventory
- PHIL : On the inventory, or in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECL (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

Sanitek Products, Inc.		Page: 16
SAFETY DATA SHEET		Revision Date: 09/07/2016
		Print Date: 8/3/2017
		SDS Number: 0000001
38-F DRIFT RETARDANT		Version: 1.5

Registration: Trade Secret

Chemical name	Identification number
ALIPHATIC HYDROCARBON	254504001-5164
POLYMER	254504001-5817

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 09/07/2016

Full text of H-Statements referred to under section 3.

H227	Combustible liquid.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H336	May cause drowsiness or dizziness.

Further information

Sources of key data used to compile the Safety Data Sheet

Key literature references and sources of data

SOLENIS Internal data

SOLENIS internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This MSDS has been prepared by the Solenis Environmental Health and Safety Department.

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization

Sanitek Products, Inc.		Page: 17
SAFETY DATA SHEET		Revision Date: 09/07/2016
		Print Date: 8/3/2017
		SDS Number: 0000001
38-F DRIFT RETARDANT		Version: 1.5

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit

P-Statement : Precautionary Statement

PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment

STEL : Short-term exposure limit

STOT : Specific Target Organ Toxicity

TLV : Threshold Limit Value

TWA : Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act

DOT : Department of Transportation

FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act

HMIRC : Hazardous Materials Information Review Commission

HMIS : Hazardous Materials Identification System

NFPA : National Fire Protection Association

NIOSH : National Institute for Occupational Safety and Health

OSHA : Occupational Safety and Health Administration

PMRA : Health Canada Pest Management Regulatory Agency

RTK : Right to Know

WHMIS : Workplace Hazardous Materials Information System