

Brandt Topcoat

Soil Wetting Agent

General Information

BRANDT TOPCOAT uses proven soil wetting technology that is safe for plants, including turf. Unlike some soil wetters that contain up to 83% water, BRANDT TOPCOAT is a 100% active mixture of components. It contains no added water.

Principal Functioning Agents

Polypropoxylated, polyethoxylated polymers and copolymer blend	100.0%
Total	100.0%

APPLICATION FREQUENCY	14 DAYS	30 DAYS	6 WEEKS	UP TO 6 MONTHS	
				SINGLE APPLICATION	SPLIT APPLICATION*
Rate per 1000 sq ft	2 oz	2 - 6 oz	3 - 9 oz	8 - 16 oz	8 oz
Rate per acre (approx)	5.5 pt	5.5 pt - 2 gal	1 - 3 gal	3 - 6 gal	3 gal
Frequency notes	Make first application at 4 oz/1000 sq ft, then normal rate thereafter	Use lower rates for non-sandy soils and higher rates for sandy soils			Apply specified amount in 2 applications, 2 weeks apart
May be applied with	Most chemicals and fertilizers. Test combination first for compatibility and safety. Generally, 4 oz or less per 1000 sq ft is compatible with most substances. Water in after application.		Should be applied alone. Water in after application.		

*Split applications will last longer than a single application.

Directions for Use

Apply with water at a rate of 2 gallons per 1000 sq ft or 100 gallons of water per acre. Effects that are more reliable are obtained with lower, more frequent applications. Irrigate before next mowing or leave clippings on ground. Test with any combination for safety and compatibility before application. Test exact combination in a small area before full-scale application. User needs to use caution and good judgment when using this and all other turf care products to avoid injury or serious damage. Seed establishment - add 4 oz. per 1000 sq ft two weeks before seeding.

BRANDT

Manufactured By:
Brandt Consolidated, Inc.
2935 South Koke Mill Road
Springfield, Illinois 62711 USA
www.brandtconsolidated.com
800.300.6559



0000-01-100

Net Contents
2.5 gal. per bottle
Packaged 2 x 2.5 gal.