

Carbomin® Potassium 0-0-24

GENERAL INFORMATION

Carbomin® Potassium 0-0-24 is designed for foliar and soil application to crops for the prevention and correction of potassium deficiencies that may limit growth and yield. **Carbomin® Potassium 0-0-24** is water dispersible and nontoxic to foliage when it is applied as directed on this label.

DIRECTIONS FOR USE MIX WELL BEFORE USING

FOLIAR APPLICATION RECOMMENDATIONS:

TREES, VINES, VEGETABLE AND FIELD CROPS: Apply **Carbomin Potassium 0-0-24** at 1-4 pints per acre (1.17-4.68 L/Hectare) in sufficient spray volume for thorough coverage (25 gallon (95 L) minimum) as needed.

SOIL APPLICATION RECOMMENDATIONS:

TREES, VINES, VEGETABLE AND FIELD CROPS: **Carbomin® Potassium 0-0-24** is recommended for use on all soil types at a rate of 1 quart to 2 gallons per acre (2.34-18.71 L/Hectare) depending on soil conditions and application methods. It should be diluted before use to ensure uniform coverage. Dilution may be made in water, compatible fertilizer solutions, or with compatible pesticides (use jar test to determine compatibility). Soil applications may be made by fertigation.

AERIAL APPLICATION RECOMMENDATIONS:

TREES, VINES, VEGETABLE AND FIELD CROPS: Apply **Carbomin® Potassium 0-0-24** at 1-2 pints per acre (1.17-2.34 L/Hectare) in sufficient spray volume for thorough coverage (10 gallon (38 L) minimum) as needed.

GUARANTEED ANALYSIS

Soluble Potash (K₂O)24.0%
Derived from: Potassium Acetate

CAUTION
KEEP OUT OF REACH OF CHILDREN
READ ENTIRE CONTAINER LABEL BEFORE USING THIS PRODUCT

COMPATIBILITY

Carbomin® Potassium 0-0-24 liquid is compatible with most fungicides, insecticides and herbicides. Some compatibility problems can occur in low pH formulations. Always check compatibility with other products prior to use.

WARRANTY AND LIMITATIONS

QualiTech, Inc. warrants that this material conforms to the chemical description on the label and is reasonably fit for the purposes referred to in the crop recommendations and the directions for use, and when this material is used in strict accordance with those recommendations and directions under normal conditions of use. QualiTech, Inc. makes no other express or implied warranties or representations, including any other express or implied warranty of fitness or merchantability. No employee or representative of QualiTech, Inc., or its distributors is authorized to do so, unless such change is made in writing with a specific reference to this warranty, and signed by an Officer of QualiTech, Inc. at its Home Office. Such warranty shall be limited to direct damages, and shall not include any consequential personal or commercial damages.

PC 7325-G6

Lab Rev: 1/29/15

LOT: XXXXXX

Manufactured for:



QualiTech, Inc., 318 Lake Hazeltine Drive, Chaska, MN 55318

Information regarding the contents and levels of metals in this product is available on the internet at <http://www.aapfco.org/metals.htm>
Carbomin® is a registered trademark of QualiTech, Inc.

NET CONTENTS: 250 Gallon Tote (946.35 Liters)
11.00 lbs/gal (1.32 kgs/liter) @ 68°F
NET WEIGHT: 2,750 lbs