

DG Lime



FEATURES & USE TIPS:

- Dispersing granule formula
- Provides calcium and magnesium, essential for plant growth
- Optimum pH levels.
- Pelletized for easy application.
- Neutralizes acidic soils

PRODUCT SPECIFICATIONS:

Ca - (30%):	Calcium
Mg - (4%):	Magnesium
CaCO₃ - (75%):	Calcium Carbonate
CCE - (90%):	Calcium Carbonate Equiv.
CaO - (42%):	Calcium Oxide
MgCO₃ - (13%):	Magnesium Carbonate
MgO - (6%):	Magnesium Oxide

Following is a specimen label that may at some point be revised or otherwise become out of date. It is intended as a guide in providing general information regarding the use of this product. Always read and follow the label on the product container.

PRODUCT CODE:

AGCDGLIME5

Date: 030410

Supersedes: 000000

Label: B10

PRODUCT CHARACTERISTICS:

Product Type:

Dispersible granular
soil enhancer

Particle Size:

SGN: 100

Net Weight:

50 lbs.


Coverage:

4,100 sq. ft.
@ Medium Rate

Andersons Golf Products is a registered trademark of The Andersons, Inc.; DG Lime is a trademark of The Andersons, Inc.

*To order, contact your local
Andersons Golf Products
distributor.*

*For more information, contact
Andersons at our website:
www.andersonsgolfproducts.com
or call 1-800-225-2639.*



DG Lime™



Dispersing Granule Technology

- Dispersing granule formula
- Provides calcium & magnesium, essential for plant growth
- Optimum pH levels
- Pelletized for easy application
- Neutralizes acidic soils

Visit our website: AndersonsGolfProducts.com

SGN 100

Net Wt 50 Lbs (22.68 kg)

Guaranteed Analysis	
Calcium (Ca)	30.00%
Magnesium (Mg)	4.00%
Calcium Carbonate (CaCO ₃)	75.00%
Calcium Carbonate Equiv. (CCE)	90.00%
Calcium Oxide (CaO)	42.00%
Magnesium Carbonate (MgCO ₃)	13.00%
Magnesium Oxide (MgO)	6.00%
Moisture content does not exceed	1.0%
Derived from dolomite	

Also contains non-plant food ingredient: lignosulfonates as Water Soluble Binder. Information regarding the contents and levels of metals in this product is available on the internet at <http://www.regulatory-info.ap.com>.

Pennsylvania, Ohio: ENP = 1,800 lbs.
Missouri: ENM = 630 lbs./ton
Iowa: Iowa Secretary of Agriculture Certified 1,500 lbs. ECCE per ton

Florida: F292, this material required 1,858 lbs. to be equal to one ton of standard agricultural liming material.

Kansas, Nebraska, Oklahoma: ECCE = 75%

Minnesota: ENP = 82%

North Carolina: 1,886 lbs. Of this material equals one ton of standard agricultural liming materials

ENV = 76%

Tennessee: RNV = 88%

New York: Effective Neutralizing Value = 76%, 1.1 tons of material needs to equal one ton of material having 100% Effective Neutralizing Value

Wisconsin: Neutralizing Index Zone = 80-89

Oregon: Lime Score = 95

Virginia: Effective Neutralizing Value = 76%

Florida Applications:
 We recommend that you follow the Florida Green Industries BMP's at <http://www.flaes.org/pdf/gifbmp07.pdf>

Directions for Use
 Apply only as directed. For use on turf and in gardens. The pellets in this product disperse immediately into the soil to reduce soil acidity and bring the soil pH levels into proper balance. When

used according to label directions, this product is non-toxic to humans, pets and plant life. For best results, determine the pH levels of the area to be treated by conducting a pH soil test. If that information is not available, refer to the recommendations below on rates and timing.

When establishing a new turf area, apply 40 lbs per 1,000 sq. ft. prior to seeding. Rake lightly into the soil. Water well after application.

For established turf areas, apply 25-40 lbs. per 1,000 sq. ft. For clay soils, apply 18 lbs. of product per 1,000 sq. ft.

To maintain proper pH soil levels, repeat application 1 to 2 times per year, or when the soil pH level drops below 6.3, at rates of 4-6 lbs. per 1,000 sq. ft.

To correct pH levels, apply 40 lbs. per 1,000 sq. ft. or 2 lbs. per 1,000 sq. ft. for every 1/10 pH correction needed.

Gardens have a deeper root zone and require a higher application rate than turf. For best results, double the turf recommended rates and mix into the soil at a depth of 6 inches.

For best results on all applications, water the area well after application.

For incorporation, after application, wet thoroughly 30 minutes before tilling.

IMPORTANT: READ BEFORE USE:
 Read the entire Directions for Use and the Warranty Disclaimer and Limitation of Liability before using this product. If terms are not acceptable, return the unopened product container at once. By using this product, user or Buyer accepts the following Warranty Disclaimer and Limitation of Liability:

WARRANTY DISCLAIMER and LIMITATION of LIABILITY:
 Manufacturer warrants that this product conforms to the chemical description on the label and is reasonably fit for the purposes stated on the label when used in strict accordance with the directions. Manufacturer makes NO OTHER EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. To the extent consistent with applicable law, it is Manufacturer's intent to LIMIT ANY LIABILITY FOR SPECIAL, CONSEQUENTIAL OR INCIDENTAL

ECONOMIC DAMAGES to refund of purchase price or replacement of product, at Buyer's choice. To the extent consistent with applicable law, manufacturer DISCLAIMS ANY LIABILITY FOR COMPENSATORY OR OTHER DAMAGES ARISING OUT OF ANY USE CONTRARY TO LABEL DIRECTIONS. Use contrary to label directions is not permitted.

LEGAL RIGHTS:

THIS LIMITED WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS; YOU MAY HAVE OTHER RIGHTS THAT VARY FROM STATE TO STATE/JURISDICTION TO STATE/JURISDICTION.


Product of USA

Distributed by:
 The Andersons Lawn Fertilizer Division, Inc.
 P. O. Box 119
 Maumee, Ohio 43537

©2010
 Andersons Golf Products is a registered trademark of The Andersons, Inc.
 DG Lime is a trademark of The Andersons, Inc.

Visit our website:
AndersonsGolfProducts.com

AGCDGLIME5
 (AGCBLKPMGRNB) - A10



Suggested Spreader Settings

These suggested spreader settings are not intended to replace calibration. Please calibrate your spreader before applying product.

SPREADER	GROUND SPEED	WIDTH OF COVERAGE	SPREADER SETTINGS		
			LIGHT RATE 2 lbs./1,000 sq. ft.	LOW RATE 4 lbs./1,000 sq. ft.	HIGH RATE 20 lbs./1,000 sq. ft.
Andersons Rotaries AccuPro 2000SR-2000 (Cone 8)	3 mph	11 feet	I	J 1/2	O 1/2
Scotts Rotaries R-8, R-8A (Cone 5)	3 mph	11 feet	G 1/2	I	N