



Fertilizer

16-2-4

Guaranteed Analysis

Total Nitrogen (N).....	16.00%
0.78% Ammoniacal Nitrogen	
15.22% Urea Nitrogen	
Available Phosphate (P ₂ O ₅).....	2.00%
Soluble Potash (K ₂ O).....	4.00%

Plant nutrients derived from ammonium phosphate, urea and potassium chloride.
Chlorine (Cl) Max 3.40%

F292

DIRECTIONS FOR USE

Apply only as directed. Apply during the growing season.

Application Rates:

LOW:	3.2 lbs/1,000 sq. ft.
MEDIUM:	4.7 lbs/1,000 sq. ft.
HIGH:	6.3 lbs/1,000 sq. ft.
HEAVY:	7.8 lbs/1,000 sq. ft.

For all applications:

- Apply to dry foliage.
- Water in after application with a minimum of 0.2 inches to help move particles into the turf canopy.
- Do not collect clippings for at least one mowing following application to avoid particle pick-up.
- Apply at the LOW or MEDIUM RATE when temperatures exceed 85°F.

Recent research has shown that well-maintained turf is an effective environmental buffer that prevents pollutants from entering our natural water bodies. To help protect these natural resources, avoid applying product to sidewalks, driveways, roadways, and other impervious surfaces. Sweep any misplaced granules back onto the area you are treating immediately after application, since storm drains often empty directly to nearby waterways.

STORAGE AND USE

Store in a clean, dry place.
Reseal opened bag by folding top down and securing.
Use only in clean, dry spreaders.
Do not leave unused product in spreaders.

IMPORTANT: READ BEFORE USE:

Read the entire Directions for Use and the Warranty Disclaimer and Limitation of Liability before using this product. If terms are not acceptable, return the unopened product container at once. By using this product, user or Buyer accepts the following Warranty Disclaimer and Limitation of Liability:

WARRANTY DISCLAIMER and LIMITATION of LIABILITY:

Manufacturer warrants that this product conforms to the chemical description on the label and is reasonably fit for the purposes stated on the label when used in strict accordance with the directions. Manufacturer makes NO OTHER EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. To the extent consistent with applicable law, it is Manufacturer's intent to LIMIT ANY LIABILITY FOR SPECIAL, CONSEQUENTIAL OR INCIDENTAL ECONOMIC DAMAGES to

refund of purchase price or replacement of product, at Buyer's choice. To the extent consistent with applicable law, Manufacturer DISCLAIMS ANY LIABILITY FOR COMPENSATORY OR OTHER DAMAGES ARISING OUT OF ANY USE CONTRARY TO LABEL DIRECTIONS. Use contrary to label directions is not permitted.

LEGAL RIGHTS:

THIS LIMITED WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS; YOU MAY HAVE OTHER RIGHTS THAT VARY FROM STATE/JURISDICTION TO STATE/JURISDICTION.

Product of U.S.A.

Manufactured by:
The Andersons Lawn Fertilizer Division, Inc.
P.O. Box 119
Maumee, OH 43537
www.andersonslawnproducts.com

The Andersons logo is a registered trademark of The Andersons, Inc.

Suggested Spreader Settings						
<i>These suggested spreader settings are not intended to replace calibration. Please calibrate your spreader prior to applying product.</i>						
50 lbs. feeds 15,600 sq. ft. (0.36 acre) with 0.50 lbs. N/1,000 sq. ft. at the LOW RATE						
50 lbs. feeds 10,600 sq. ft. (0.24 acre) with 0.75 lbs. N/1,000 sq. ft. at the MEDIUM RATE						
50 lbs. feeds 7,900 sq. ft. (0.18 acre) with 1.00 lbs. N/1,000 sq. ft. at the HIGH RATE						
50 lbs. feeds 6,400 sq. ft. (0.15 acre) with 1.25 lbs. N/1,000 sq. ft. at the HEAVY RATE						
SPREADER	GROUND SPEED	WIDTH OF COVERAGE	SPREADER SETTINGS			
			LOW RATE 3.2 lbs. per 1,000 sq. ft.	MEDIUM RATE 4.7 lbs. per 1,000 sq. ft.	HIGH RATE 6.3 lbs. per 1,000 sq. ft.	HEAVY RATE 7.8 lbs. per 1,000 sq. ft.
Andersons AccuPro 2000, SR-2000 (cone 4)	3 mph	12 feet	K 1/2	M 1/4	N 3/4	P
Scotts R-8A (cone 4)	3 mph	12 feet	J	K 1/2	M	N 1/2
Lesco Broadcast (020093)	3 mph	12 feet	E 3/4	F 1/2	G 1/4	H
Lesco Broadcast (705698)	3 mph	12 feet	13 3/4	14 1/2	16 1/4	18
Lely Models WTR, WFR, HR, 1250 (PTO at 450 rpm) Pattern II-A	4.5 mph	40 feet	4 1/2	5 1/4	6 1/4	7
Vicon (03 Series)	4.5 mph	36 feet	28	33	39	44

SGN 215
Net Wt. 50 Lbs. (22.68 kg)



APT1650

G8 (APTBLKPMGRNB)