

Fertilizer 18-12-10



FEATURES & USE TIPS:

- Utilizes NS-54™ proprietary coated slow release nitrogen to provide uniform growth with extended nitrogen feeding.
- Provides phosphate for use in new seeding, overseeding, sodding and sprigging operations.
- SGN 215 for use on fairways, roughs and other turf areas.

PRODUCT SPECIFICATIONS:

N (18%): 4.69% Ammoniacal Nitrogen
13.31% Urea Nitrogen*
*4.50 Slowly available nitrogen from Polymer Coated Sulfur Coated Urea

P - as P_2O_5 (12%): Ammonium Phosphate

K - as (K_2O) (10%): Potassium Chloride

Cl (8.46%): Maximum Chlorine

Following is a specimen label that may at some point be revised or otherwise become out of date. It is intended as a guide in providing general information regarding the use of this product. Always read and follow the label on the product container.

PRODUCT CODE:

APT18450

Date: 010710
Supersedes: 000000
Label: E8

PRODUCT CHARACTERISTICS:

Product Type:
Fertilizer

Nitrogen Type:
NS-54™

Particle Size:
SGN: 215

Net Weight:
50 lbs.

Coverage:
8,900 sq. ft.
@ Medium Rate

Bags / Pallet:
45

The Andersons logo is a registered trademark of The Andersons, Inc.; NS-54 is a trademark of The Andersons, Inc.

To order, contact your local Andersons Lawn Products distributor.

*For more information, contact Andersons at our website:
www.andersonslawnproducts.com
or call 1-800-225-2639.*



Turf Products

Fertilizer

18-12-10

- Contains NS-54™ coated slow release nitrogen to provide uniform growth with extended nitrogen feeding.
- SGN 215 for use on fairways, roughs and other turf areas

GUARANTEED ANALYSIS

Total Nitrogen (N)	18.00%
4.69% Ammoniacal Nitrogen	
13.31% Urea Nitrogen*	
Available Phosphate (P ₂ O ₅)	12.00%
Soluble Potash (K ₂ O)	10.00%
Plant nutrients derived from urea, ammonium phosphate, potassium chloride and polymer coated sulfur coated urea.	
Chlorine (Cl) Max	8.46%

*4.50% Slowly available nitrogen from polymer coated sulfur coated urea.

F292

GENERAL INFORMATION

The Andersons Turf Products Fertilizer 18-12-10 provides grass with nitrogen, phosphorus and potash for maintaining strong, vigorous turf.

The nitrogen in this product is both readily and slowly available which makes this product excellent for applications throughout the growing season when the minimum soil temperatures are greater than 55°F to 60°F and not exceeding 85°F.

This product is dust free and free flowing. The uniform particle sizing assures easy and accurate applications.

WHEN AND HOW TO USE

In the spring, or as soon as weather and ground conditions permit, apply 2.8 to 7.0 pounds of this product per 1,000 square feet. Repeat every six to eight weeks, or as necessary, throughout the growing season.

To ensure that you have the best possible fertilization program, use fertilizers in conjunction with a soil and tissue test program operated by a state certified laboratory familiar with the soils of your region. Cooperative extension agents can provide the names of recommended labs in your area.

Apply only as directed.

Recent research has shown that well-maintained turf is an effective environmental buffer that prevents pollutants from entering our natural water bodies. To help protect these natural resources, please avoid applying product to sidewalks, driveways, roadways, and other impervious surfaces which are adjacent to storm drains. Sweep any misplaced granules back onto the area you are treating immediately after application, since storm drains often empty directly to nearby waterways.

IMPORTANT: READ BEFORE USE:

Read the entire Directions for Use and the Warranty Disclaimer and Limitation of Liability before using this product. If terms are not acceptable, return the unopened product container at once. By using this product, user or Buyer accepts the following Warranty Disclaimer and Limitation of Liability:

WARRANTY DISCLAIMER AND LIMITATION OF LIABILITY:

Manufacturer warrants that this product conforms to the chemical description on the label and is reasonably fit for the purposes stated on the label when used in strict accordance with the directions. Manufacturer makes NO OTHER EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. To the extent consistent with applicable law, it is Manufacturer's intent to LIMIT ANY LIABILITY FOR SPECIAL, CONSEQUENTIAL OR INCIDENTAL ECONOMIC DAMAGES to refund of purchase price or replacement of product, at Buyer's choice. To the extent consistent with applicable law, Manufacturer DISCLAIMS ANY LIABILITY FOR COMPENSATORY OR OTHER DAMAGES ARISING OUT OF ANY USE CONTRARY TO LABEL DIRECTIONS. Use contrary to label directions is not permitted.

LEGAL RIGHTS:

THIS LIMITED WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS; YOU MAY HAVE OTHER RIGHTS THAT VARY FROM STATE/JURISDICTION TO STATE/JURISDICTION.


Product of U.S.A.

Manufactured by:
The Andersons Lawn Fertilizer Division, Inc.
P.O. Box 119
Maumee, OH 43537
www.andersonslawnproducts.com

The Andersons logo is a registered trademark of The Andersons, Inc.; NS-54 is a trademark of The Andersons, Inc.

Suggested Spreader Settings						
Suggested spreader settings are not intended to replace calibration. Please calibrate your spreader prior to applying product.						
50 lbs. feeds 17,800 sq. ft. (0.41 acre) with 0.50 lbs. N/1,000 sq. ft. at the LIGHT RATE						
50 lbs. feeds 11,900 sq. ft. (0.27 acre) with 0.75 lbs. N/1,000 sq. ft. at the LOW RATE						
50 lbs. feeds 8,900 sq. ft. (0.20 acre) with 1.00 lbs. N/1,000 sq. ft. at the MEDIUM RATE						
50 lbs. feeds 7,100 sq. ft. (0.16 acre) with 1.26 lbs. N/1,000 sq. ft. at the HIGH RATE						
SPREADER	GROUND SPEED	WIDTH OF COVERAGE	SPREADER SETTINGS			
			LIGHT RATE 2.8 lbs. per 1,000 sq. ft.	LOW RATE 4.2 lbs. per 1,000 sq. ft.	MEDIUM RATE 5.6 lbs. per 1,000 sq. ft.	HIGH RATE 7.0 lbs. per 1,000 sq. ft.
Andersons AccuPro2000, SR-2000 (cone 3)	3 mph	12 feet	J 1/2	K 1/2	L 3/4	N 1/4
Scotts R-8A (cone 3)	3 mph	12 feet	J 1/4	L 1/4	M 1/4	N
Lely Models WTR, WFR, HR, 1250 (PTO at 450 rpm) Pattern III-A	4.5 mph	26 feet	3 1/2	4 1/4	4 3/4	5 1/4
Vicon (Q3 Series)	4.5 mph	38 feet	17	25	29	33

SGN 215
Net Wt. 50 Lbs. (22.68 kg)



APT18450

E8 (APTBCLKPMGRNB)