

ContecDG[®] Dispersing Granule Technology 20-0-10



FEATURES & USE TIPS:

- Patented dispersing granule formula
- Greatly reduces fertilizer loss due to ball, shoe & mower pickup.
- SGN 75 - ideal for greens use.
- 75% of the nitrogen is from MUTECH[™] controlled release N.

PRODUCT SPECIFICATIONS:

N - (20%): 6.89% urea nitrogen
7.67% other water soluble nitrogen*
5.44% water insoluble nitrogen
*7.67% slowly available nitrogen
from methylene ureas

K - as K₂O - (10%): Potassium sulfate

Mn - (7.00%): Total Manganese

S - (3.40%): Combined Sulfur

PRODUCT CODE:

AGC2015WMDG4

Date: 071409
Supersedes: 121907
Label: G9

PRODUCT CHARACTERISTICS:

Product Type:
Fertilizer

Nitrogen Type:
MUTECH[™] methylene
urea

Particle Size:
SGN: 75

Net Weight:
40 lbs.

Coverage:
13,300 sq. ft.
@ Medium Rate

Andersons Golf Products and ContecDG[®] are registered trademarks of The Andersons, Inc.; MUTECH is a trademark of The Andersons, Inc.

*To order, contact your local
Andersons Golf Products
distributor.*

*For more information, contact
Andersons at our website:
www.andersonsgolfproducts.com or
www.contecdg.com
or call 1-800-225-2639.*

Following is a specimen label that may at some point be revised or otherwise become out of date. It is intended as a guide in providing general information regarding the use of this product. Always read and follow the label on the product container.

PRODUCT SHEET



20-0-10

GUARANTEED ANALYSIS

Total Nitrogen (N)	20.00%
6.89% Urea Nitrogen	
5.44% Water Insoluble Nitrogen	
7.67% Other Water Soluble Nitrogen*	
Soluble Potash (K ₂ O)	10.00%
Sulfur (S)	3.40%
3.40% Combined Sulfur (S)	
Manganese (Mn)	7.00%
7.00% Water Soluble Manganese (Mn)	

Plant nutrients derived from urea, methylene ureas, potassium sulfate and manganese sulfate.

*7.67% slowly available nitrogen from methylene ureas

U.S. Patent #6,884,756

Information regarding the contents and levels of metals in this product is available on the internet at <http://www.regulatory-info-ap.com>

DIRECTIONS FOR USE
Apply only as directed during the growing season.

For use on greens and tees where a nitrogen and potassium application is desired. Potassium application will help to improve turfgrass resistance to stress. High manganese to correct deficiencies and improve turf color.

Watering in this product will disperse each granule into thousands of particles. This will facilitate the movement of the nutrients into the soil. This particle dispersion will greatly reduce ball, shoe and mower pickup - minimizing nutrient loss.

Application to wet, close-cut golf turf may result in foliar staining, which will discolor the turf to a brown/black appearance. This can occur even if immediate irrigation or rainfall occurs. It is recommended that this product be applied to dry turf only.

Application Rates:

LOW:	1.5 lbs/1,000 sq. ft.
MEDIUM:	3.0 lbs/1,000 sq. ft.
HIGH:	4.5 lbs/1,000 sq. ft.

FLORIDA APPLICATIONS: We recommend that you follow the Florida Green Industries BMP's at http://www.flaes.org/pdf/BMP_Book_final.pdf

FLORIDA APPLICATIONS: We recommend that you follow the Florida Golf Course BMP's at <http://www.flaes.org/pdf/glfbmp07.pdf>

For all applications:

- Apply to dry turf and water in immediately with 0.1 to 0.2 inches of water.
- Apply at the MEDIUM RATE to HIGH RATE.
- Exception: Apply at the LOW RATE if temperatures are 85°F (30°C) or above. Make repeat applications as necessary.

Recent research has shown that well-maintained turf is an effective environmental buffer that prevents pollutants from entering our natural water bodies. To help protect these natural resources, avoid applying product to sidewalks, driveways, roadways, and other impervious surfaces. Sweep any misplaced granules back onto the area you are treating immediately after application, since storm drains often empty directly to nearby waterways.

Storage and Use:

Store in a clean, dry place.
Reseal opened bag by folding top down and securing.
Use only clean, dry spreaders.
Do not leave unused product in spreaders.

IMPORTANT: READ BEFORE USE:

Read the entire Directions for Use and the Warranty Disclaimer and Limitation of Liability before using this product. If terms are not acceptable, return the unopened product container at once. By using this product, user or Buyer accepts the following Warranty Disclaimer and Limitation of Liability:

WARRANTY DISCLAIMER AND LIMITATION OF LIABILITY:

Manufacturer warrants that this product conforms to the chemical description on the label and is reasonably fit for the purposes stated on the label when used in strict accordance with the directions.
Manufacturer makes NO OTHER EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. To the extent consistent with applicable law, it is Manufacturer's intent to LIMIT ANY LIABILITY FOR SPECIAL, CONSEQUENTIAL OR INCIDENTAL ECONOMIC DAMAGES to refund of purchase price or replacement of product, at Buyer's choice. To the extent consistent with applicable law, Manufacturer DISCLAIMS ANY LIABILITY FOR COMPENSATORY OR OTHER DAMAGES ARISING OUT OF ANY USE CONTRARY TO LABEL DIRECTIONS. Use contrary to label directions is not permitted.

LEGAL RIGHTS:

THIS LIMITED WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS; YOU MAY HAVE OTHER RIGHTS THAT VARY FROM STATE/JURISDICTION TO STATE/JURISDICTION.

Product of USA

Manufactured by:
The Andersons Lawn Fertilizer Division, Inc.
P.O. Box 119
Maumee, Ohio 43537
www.andersonsgolfproducts.com

Andersons Golf Products and ContecDG are registered trademarks of The Andersons, Inc.

Suggested Spreader Settings


These suggested spreader settings are not intended to replace calibration. Please calibrate your spreader before applying product.

40 lbs. feeds 22,600 sq. ft. (0.61 acre) with 0.30 lb. N/1,000 sq. ft. at the LOW RATE (1.5 lbs/1,000 sq. ft.)
40 lbs. feeds 13,300 sq. ft. (0.31 acre) with 0.60 lb. N/1,000 sq. ft. at the MEDIUM RATE (3.0 lbs/1,000 sq. ft.)
40 lbs. feeds 8,900 sq. ft. (0.20 acre) with 0.90 lb. N/1,000 sq. ft. at the HIGH RATE (4.5 lbs/1,000 sq. ft.)

SPREADER	GROUND SPEED	WIDTH OF COVERAGE	SPREADER SETTINGS		
			LOW RATE 1.5 lbs/1,000 sq. ft.	MEDIUM RATE 3.0 lbs/1,000 sq. ft.	HIGH RATE 4.5 lbs/1,000 sq. ft.
Andersons AccuPro 2000, SR-2000 (cone 9)	3 mph	9 feet	I	J 3/4	L 1/2
Scotts R-8, R-8A (cone 6)	3 mph	9 feet	H	I 1/4	K
Andersons SS-2 Drop	3 mph	overlap wheels	3	4	5
Lely Models WTR, WFR, HR, 1250 (PTO at 450 rpm) (Pattern III-A)	4.5 mph	26 feet	3 3/4	4 1/2	5 1/2
Vicon (03 Series)	4.5 mph	15 feet	11	14	17

SGN 75

Net Wt 40 Lbs (18.14 kg)



AGC2015WMDG4

G9 (AGCBLKPCDGB)