

# ContecDG<sup>®</sup>

## Dispersing Granule Technology

# 24-0-10



### FEATURES & USE TIPS:

- Patented dispersing granule formula
- Greatly reduces fertilizer loss due to ball, shoe & mower pickup.
- SGN 150 - ideal for fairways use.
- 90% of the nitrogen is from MUTECH-L™ controlled release N, a longer lasting version of MUTECH methylene urea.

### PRODUCT SPECIFICATIONS:

**N - (24%):** 2.40% ammoniacal nitrogen  
1.86% urea nitrogen  
6.81% other water soluble nitrogen\*  
12.93% water insoluble nitrogen  
\*6.81% slowly available nitrogen  
from methylene ureas

**K - as K<sub>2</sub>O - (10%):** Potassium sulfate

**S - (6.15%):** Combined Sulfur

### PRODUCT CODE:

## AGC2424WDG5.1

Date: 030310

Supersedes: 121708

Label: G9

### PRODUCT CHARACTERISTICS:

#### **Product Type:**

Dispersible granular nutrient

#### **Nitrogen Type:**

MUTECH-L™ methylene urea

#### **Particle Size:**

SGN: 150

#### **Net Weight:**

50 lbs.

#### **Coverage:**

6,800 sq. ft.  
@ Medium Rate

Andersons Golf Products and ContecDG<sup>®</sup> are registered trademarks of The Andersons, Inc.; MUTECH is a trademark of The Andersons, Inc.

*To order, contact your local  
Andersons Golf Products  
distributor.*

*For more information, contact  
Andersons at our website:  
[www.andersonsgolfproducts.com](http://www.andersonsgolfproducts.com)  
or call 1-800-225-2639.*

*Following is a specimen label that may at some point be revised or otherwise become out of date. It is intended as a guide in providing general information regarding the use of this product. Always read and follow the label on the product container.*

**PRODUCT SHEET**



# 24-0-10

- Patented dispersing granules that greatly reduce mower pickup
- Contains MUTECH-L™ for extended feeding
- Specially designed for use on fairways & other turf areas

## GUARANTEED ANALYSIS

|                                         |        |
|-----------------------------------------|--------|
| Total Nitrogen (N) .....                | 24.00% |
| 2.40% Ammoniacal Nitrogen .....         |        |
| 1.86% Urea Nitrogen .....               |        |
| 12.93% Water Insoluble Nitrogen .....   |        |
| 6.81% Other Water Soluble Nitrogen*     |        |
| Soluble Potash (K <sub>2</sub> O) ..... | 10.00% |
| Sulfur (S) .....                        | 6.15%  |
| 6.15% Combined Sulfur (S) .....         |        |

Plant nutrients derived from methylene ureas, ureaform, ammonium sulfate and potassium sulfate.

\*6.81% Slowly available nitrogen from methylene ureas and ureaform.

U.S. Patent #6,884,756

Information regarding the contents and levels of metals in this product is available on the internet at <http://www.regulatory-info-ap.com>

## DIRECTIONS FOR USE

Apply only as directed during the growing season.

Use Andersons Golf Products ContecDG® Dispensing Granule Technology 24-0-10 for fairways and other turf areas where a high nitrogen and potassium fertilization is desired.

Watering in this product will disperse each granule into thousands of particles. This will facilitate the movement of the nutrients into the soil. This particle dispersion will also eliminate ball, shoe and mower pickup - minimizing nutrient loss.

## Application Rates:

|         |                        |
|---------|------------------------|
| LIGHT:  | 4.16 lbs/1,000 sq. ft. |
| LOW:    | 6.25 lbs/1,000 sq. ft. |
| MEDIUM: | 7.29 lbs/1,000 sq. ft. |
| HIGH:   | 8.33 lbs/1,000 sq. ft. |

**FLORIDA APPLICATIONS:** We recommend that you follow the Florida Green Industries BMP's at [http://www.flaes.org/pdf/BMP\\_Book\\_Final.pdf](http://www.flaes.org/pdf/BMP_Book_Final.pdf)

**FLORIDA APPLICATIONS:** We recommend that you follow the Florida Golf Course BMP's at <http://www.flaes.org/pdf/glbmp07.pdf>

**For all applications:** Immediately after application, for optimum results, apply a minimum of 0.2 inches of water to disperse the granules.

Recent research has shown that well-maintained turf is an effective environmental buffer that prevents pollutants from entering our natural water bodies. To help protect these natural resources, avoid applying product to sidewalks, driveways, roadways, and other impervious surfaces. Sweep any misplaced granules back onto the area you are treating immediately after application, since storm drains often empty directly to nearby waterways.

## Spreading with PTO driven spreaders:

Excessive agitation of Contec DG can result in damage to the Contec DG particles. Keep the PTO operating at 540 rpm or less. DO NOT use agitation bars or stir bars, as this can result in the premature breakdown of Contec DG granules.

## Spreader Settings:

Spreader settings are recommendations only and should be considered as a beginning point for user calibration. Results obtained by an applicator in the field may be different due to spreader production variations, spreader calibration differences, operating variables, and environmental factors (temperature, humidity, etc.). It is recommended that applicators check the pattern and delivery rate for their particular spreader periodically under their operating conditions using the actual product to be applied.

## Storage and Use:

Store in a clean, dry place.  
Reseal opened bag by folding top down and securing.  
Use only clean, dry spreaders.  
Do not leave unused product in spreaders.

## IMPORTANT: READ BEFORE USE:

Read the entire Directions for Use and the Warranty Disclaimer and Limitation of Liability before using this product. If terms are not acceptable, return the unopened product container at once. By using this product, user or Buyer accepts the following Warranty Disclaimer and Limitation of Liability:

## WARRANTY DISCLAIMER and LIMITATION of LIABILITY:

Manufacturer warrants that this product conforms to the chemical description on the label and is reasonably fit for the purposes stated on the label when used in strict accordance with the directions. Manufacturer makes NO OTHER EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. To the extent consistent with applicable law, it is Manufacturer's intent to LIMIT ANY LIABILITY FOR SPECIAL, CONSEQUENTIAL OR INCIDENTAL ECONOMIC DAMAGES to refund of purchase price or replacement of product, at Buyer's choice. To the extent consistent with applicable law, Manufacturer DISCLAIMS ANY LIABILITY FOR COMPENSATORY OR OTHER DAMAGES ARISING OUT OF ANY USE CONTRARY TO LABEL DIRECTIONS. Use contrary to label directions is not permitted.

## LEGAL RIGHTS:

THIS LIMITED WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS; YOU MAY HAVE OTHER RIGHTS THAT VARY FROM STATE/JURISDICTION TO STATE/JURISDICTION.

Product of USA

Manufactured by:  
The Andersons Lawn Fertilizer Division, Inc.  
P. O. Box 119  
Maumee, Ohio 43537  
[www.andersonsgolfproducts.com](http://www.andersonsgolfproducts.com)

Andersons Golf Products and Contec DG are registered trademarks of The Andersons, Inc.; MUTECH is a trademark of The Andersons, Inc.

## Suggested Spreader Settings

These suggested spreader settings are not intended to replace calibration.

Please calibrate your spreader before applying product.

|                                                                                                                   |
|-------------------------------------------------------------------------------------------------------------------|
| 50 lbs. feeds 12,000 sq. ft. (0.28 acre) with 1.00 lb. N/1,000 sq. ft. at the LIGHT RATE (4.16 lbs/1,000 sq. ft.) |
| 50 lbs. feeds 8,000 sq. ft. (0.18 acre) with 1.50 lb. N/1,000 sq. ft. at the LOW RATE (6.25 lbs/1,000 sq. ft.)    |
| 50 lbs. feeds 6,800 sq. ft. (0.16 acre) with 1.75 lb. N/1,000 sq. ft. at the MEDIUM RATE (7.29 lbs/1,000 sq. ft.) |
| 50 lbs. feeds 6,000 sq. ft. (0.14 acre) with 2.00 lb. N/1,000 sq. ft. at the HIGH RATE (8.33 lbs/1,000 sq. ft.)   |

| SPREADER                                                        | GROUND SPEED | WIDTH OF COVERAGE | LIGHT RATE<br>4.16 lbs/1,000 sq. ft. | LOW RATE<br>6.25 lbs/1,000 sq. ft. | MEDIUM RATE<br>7.29 lbs/1,000 sq. ft. | HIGH RATE<br>8.33 lbs/1,000 sq. ft. |
|-----------------------------------------------------------------|--------------|-------------------|--------------------------------------|------------------------------------|---------------------------------------|-------------------------------------|
|                                                                 |              |                   |                                      |                                    |                                       |                                     |
| Andersons AccuPro 2000, SR-2000 (cone 5)                        | 3 mph        | 11 feet           | M 1/4                                | O 1/4                              | P 1/4                                 | Q 1/4                               |
| Scotts R-8, R-8A (cone 5)                                       | 3 mph        | 11 feet           | K 3/4                                | N 1/4                              | O 1/4                                 | P 1/4                               |
| Lely Models WTR, WFR, HR, 1250 (PTO at 450 rpm) (Pattern III-C) | 4.5 mph      | 34 feet           | 5 3/4                                | 6 3/4                              | 7 1/4                                 | 7 3/4                               |
| Vicon (O3 Series)                                               | 4.5 mph      | 20 feet           | 20                                   | 26                                 | 28                                    | 31                                  |

## SGN 150

Net Wt. 50 Lbs (22.68 kg)



# AGC2424WDG5.1

G9 (AGCBLKPLCDGB)