

Fertilizer 43-0-0



FEATURES & USE TIPS:

- Contains NS-54™ polymer coated sulfur coated urea
- SGN 215
- Feeds turf with a steady supply of nitrogen over an extended period.
- Two-tiered encapsulation process enables the nitrogen to be released accurately.
- Provides quick turf response without extra mowing

PRODUCT SPECIFICATIONS:

N - (43%):	Urea Nitrogen* *43.00% Slowly available nitrogen from polymer coated sulfur coated urea
S - (4.00%):	Free Sulfur

Following is a specimen label that may at some point be revised or otherwise become out of date. It is intended as a guide in providing general information regarding the use of this product. Always read and follow the label on the product container.

PRODUCT CODE:

AGC4315

Date: 012110
Supersedes: 000000

PRODUCT CHARACTERISTICS:

Product Type:
Fertilizer

Nitrogen Type:
NS-54

Particle Size:
SGN: 215

Net Weight:
50 lbs.

Coverage:
14,200 sq. ft.
@ Medium Rate

Andersons Golf Products is a registered trademark of The Andersons, Inc.; NS-54 is a trademark of The Andersons, Inc.

*To order, contact your local
Andersons Golf Products
distributor.*

*For more information, contact
Andersons at our website:
www.andersonsgolfproducts.com
or call 1-800-225-2639.*



Andersons
GOLF PRODUCTS®

Fertilizer

43-0-0

with NS-54™ Nitrogen

- Contains controlled release nitrogen for extended feeding
- Provides initial green-up along with minimal surge growth

Visit our website: AndersonsGolfProducts.com

SGN 215

Net Wt. 50 Lbs. (22.68 kg)



Fertilizer 43-0-0

with NS-54™ Nitrogen

GUARANTEED ANALYSIS

Total Nitrogen (N)	43.00%
43.00% Urea Nitrogen*	
Sulfur (S)	4.00%
4.00% Free Sulfur (S)	

Plant nutrients derived from polymer coated sulfur coated urea.

*43.00% slowly available nitrogen from polymer coated sulfur coated urea.

F292

Information regarding the contents and levels of metals in this product is available on the internet at <http://www.regulatory-info-ap.com>

DIRECTIONS FOR USE

Apply only as directed. Use this product on actively growing fairways and roughs whenever a high nitrogen feeding with quick green-up and controlled-release nitrogen are desired.

Application Rates:

LIGHT:	2.3 lbs./1,000 sq. ft.
LOW:	2.9 lbs./1,000 sq. ft.
MEDIUM:	3.5 lbs./1,000 sq. ft.
HIGH:	4.1 lbs./1,000 sq. ft.

For all applications:

- For use on fairways and roughs.
- DO NOT USE ON GREENS OR OTHER LOW-CUT TURF.
- Do not apply with a drop-type spreader.
- Apply to dry foliage.
- Water in after application with a minimum of 0.2 inches to help move particles into the turf canopy.
- Do not collect clippings for at least one mowing following application to avoid particle pick-up.
- For cool season grasses, apply at the LIGHT RATE in mid-summer when temperatures are above 80°F.
- For warm season grasses, apply at LIGHT RATE during mid-summer when temperatures are extreme (90°F or above).

Recent research has shown that well-maintained turf is an effective environmental buffer that prevents pollutants from entering our natural water bodies. To help protect these natural resources, avoid applying product to sidewalks, driveways, roadways, and other impervious surfaces. Sweep any misplaced granules back onto the area you are treating immediately after application, since storm drains often empty directly to nearby waterways.

Storage and Use:

Store in a clean, dry place.
Reseal opened bag by folding top down and securing.
Use only clean, dry spreaders.
Do not leave unused product in spreaders.

IMPORTANT: READ BEFORE USE:

Read the entire Directions for Use and the Warranty Disclaimer and Limitation of Liability before using this product. If terms are not acceptable, return the unopened product container at once. By using this product, user or Buyer accepts the following Warranty Disclaimer and Limitation of Liability:

WARRANTY DISCLAIMER and LIMITATION of LIABILITY:

Manufacturer warrants that this product conforms to the chemical description on the label and is reasonably fit for the purposes stated on the label when used in strict accordance with the directions. Manufacturer makes NO OTHER EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. To the extent consistent with applicable law, it is Manufacturer's intent to LIMIT ANY LIABILITY FOR SPECIAL, CONSEQUENTIAL OR INCIDENTAL ECONOMIC DAMAGES to refund of purchase price or replacement of product, at Buyer's choice. To the extent consistent with applicable law, manufacturer DISCLAIMS ANY LIABILITY FOR COMPENSATORY OR OTHER DAMAGES ARISING OUT OF ANY USE CONTRARY TO LABEL DIRECTIONS. Use contrary to label directions is not permitted.

LEGAL RIGHTS:

THIS LIMITED WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS; YOU MAY HAVE OTHER RIGHTS THAT VARY FROM STATE/JURISDICTION TO STATE/JURISDICTION.

Product of U.S.A.

Manufactured by:
The Andersons Lawn Fertilizer Division, Inc.
P. O. Box 119
Maumee, Ohio 43537

AGC4315
AGC4315B

©2008

Andersons Golf Products is a registered trademark of The Andersons, Inc.; NS-54 is a trademark of The Andersons, Inc.

Visit our website: AndersonsGolfProducts.com

FPO: UPC
0 31865 - 31104 - 8

Suggested Spreader Settings

These suggested spreader settings are not intended to replace calibration.

Please calibrate your spreader before applying product.

50 lbs. feeds 21,700 sq. ft. (0.50 acre) with 0.99 lbs. N/1,000 sq. ft. at the LIGHT RATE (2.3 lbs./1,000 sq. ft.)
50 lbs. feeds 17,200 sq. ft. (0.39 acre) with 1.24 lbs. N/1,000 sq. ft. at the LOW RATE (2.9 lbs./1,000 sq. ft.)
50 lbs. feeds 14,200 sq. ft. (0.33 acre) with 1.50 lbs. N/1,000 sq. ft. at the MEDIUM RATE (3.5 lbs./1,000 sq. ft.)
50 lbs. feeds 12,100 sq. ft. (0.28 acre) with 1.76 lbs. N/1,000 sq. ft. at the HIGH RATE (4.1 lbs./1,000 sq. ft.)

			SPREADER SETTINGS			
SPREADER	GROUND SPEED	WIDTH OF COVERAGE	LIGHT RATE	LOW RATE	MEDIUM RATE	HIGH RATE
Andersons AccuPro 2000/ SR-2000 (Cone 2)	3 mph	10 feet	J 3/4	K 1/4	L	L 1/2
Andersons AccuPro 1000	3 mph	10 feet	J 3/4	K 1/4	L	L 1/2
Scotts Rotaries R-8, R-8A (Cone 2)	3 mph	10 feet	I 1/2	J	J 1/2	K
Lely Models (Pattern II-A) WTR, WFR, HR, 1250 (PTO at 450 rpm)	4.5 mph	28 feet	4 1/4	4 1/2	4 3/4	5
Vicon (03 Series-Standard Spout)	4.5 mph	26 feet	25	28	30	33