

46-0-0



**Turf Products
Fertilizer**

FEATURES & USE TIPS:

- This product has been optimized for application using a liquid sprayer
- 100% of the total nitrogen is treated with NutriSphere-N®
- NutriSphere-N is a proprietary nitrogen management tool that has been shown to prolong desirable turf color up to eight weeks.
- SGN 215 for use on fairways, roughs, home lawns and other turf areas.

PRODUCT SPECIFICATIONS:

N (46%): Urea Nitrogen

PRODUCT CODE:

APT4650

Date: 010610
Supersedes: 000000
Label: F9

PRODUCT CHARACTERISTICS:

Product Type:
Fertilizer

Nitrogen Type:
NutriSphere-N

Particle Size:
SGN: 150

Net Weight:
50 lbs.

Coverage:
15,100 sq. ft. @ Medium
Rate

Bags / Pallet:
45

Following is a specimen label that may at some point be revised or otherwise become out of date. It is intended as a guide in providing general information regarding the use of this product. Always read and follow the label on the product container.

The Andersons logo is a registered trademark of The Andersons, Inc.; NutriSphere is a registered trademark of Specialty Fertilizer Products, LLC.

*To order, contact your local
Andersons Lawn Products
distributor.*

*For more information, contact
Andersons at our website:
www.andersonslawnproducts.com
or call 1-800-225-2639.*



Fertilizer

Turf Products

46-0-0

- Contains NutriSphere-N®

Guaranteed Analysis

Total Nitrogen (N)..... 46.00%
46.00% Urea Nitrogen

Plant nutrients derived from urea.

F292

Information regarding the contents and levels of metals in this product is available on the internet at <http://www.regulatory-info-ap.com>

DIRECTIONS FOR USE

Apply only as directed. Apply during the growing season.

General Information

This product is designed primarily for application in spray equipment. It can also be spread as a dry product using traditional rotary spreaders, but it is not optimized for dry spreading application.

Liquid Application for Spray Equipment Application Rates

Desired rate of nitrogen (lb/1,000 sq. ft.)	Amount of product per 1,000 sq. ft.	Amount of product per Acre
0.25	0.5	24
0.50	1.1	47
0.75	1.6	71
1.00	2.2	95
1.25	2.7	118

When using in spray equipment, be sure to use enough water to properly dissolve the product. Also use adequate agitation. Product not properly dissolved may not spray accurately. Be sure the sprayer to be used is properly calibrated and in good working order.

Dry Application

LIGHT RATE: 2.2 lbs/1,000 sq. ft.
LOW RATE: 2.8 lbs/1,000 sq. ft.
MEDIUM RATE: 3.3 lbs/1,000 sq. ft.
HIGH RATE: 3.8 lbs/1,000 sq. ft.

We recommend that you follow the Florida Green Industries BMP's at: http://www.flaes.org/pdf/BMP_Book_final.pdf

We recommend that you follow the Florida Golf Course BMP's at: <http://www.flaes.org/pdf/gfbmp07.pdf>

For all applications:

- Apply to dry foliage.
- Water in after application with a minimum of 0.2 inches to help move particles into the turf canopy.
- Do not collect clippings for at least one mowing following application to avoid particle pick-up.

Cool Season Grasses:

- Apply at the LOW or MEDIUM RATE.
- Apply at the LIGHT RATE when temperatures exceed 85°F.

Warm Season Grasses:

- Apply at the LOW to HIGH RATE every 4-6 weeks during the period of active growth.

Recent research has shown that well-maintained turf is an effective environmental buffer that prevents pollutants from entering our natural water bodies. To help protect these natural resources, avoid applying product to sidewalks, driveways, roadways, and other impervious surfaces. Sweep any misplaced granules back onto the area you are treating immediately after application, since storm drains often empty directly to nearby waterways.

STORAGE AND USE

Store in a clean, dry place.
Reseal opened bag by folding top down and securing.
Use only clean, dry spreaders.
Do not leave unused product in spreaders.

IMPORTANT: READ BEFORE USE:

Read the entire Directions for Use and the Warranty Disclaimer and Limitation of Liability before using this product. If terms are not acceptable, return the unopened product container at once. By using this product, user or Buyer accepts the following Warranty Disclaimer and Limitation of Liability:

WARRANTY DISCLAIMER and LIMITATION of LIABILITY:

Manufacturer warrants that this product conforms to the chemical description on the label and is reasonably fit for the purposes stated on the label when used in strict accordance with the directions. Manufacturer makes NO OTHER EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. To the extent consistent with applicable law, it is Manufacturer's intent to LIMIT ANY LIABILITY FOR SPECIAL, CONSEQUENTIAL OR INCIDENTAL ECONOMIC DAMAGES to refund of purchase price or replacement of product, at Buyer's choice. To the extent consistent with applicable law, Manufacturer DISCLAIMS ANY LIABILITY FOR COMPENSATORY OR OTHER DAMAGES ARISING OUT OF ANY USE CONTRARY TO LABEL DIRECTIONS. Use contrary to label directions is not permitted.

LEGAL RIGHTS:

THIS LIMITED WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS; YOU MAY HAVE OTHER RIGHTS THAT VARY FROM STATE/JURISDICTION TO STATE/JURISDICTION.

Product of U.S.A.

Manufactured by:
The Andersons Lawn Fertilizer Division, Inc.
P.O. Box 119
Maumee, OH 43537
www.andersonslawnproducts.com

The Andersons logo is a registered trademark of The Andersons, Inc.; NutriSphere is a registered trademark of Specialty Fertilizer Products, LLC.

Suggested Spreader Settings

These suggested spreader settings are not intended to replace calibration. Please calibrate your spreader before applying product.

50 lbs./hect (22,700 sq. ft. (0.32 acres) with 1,000 lbs. N/1,000 sq. ft. at the LIGHT RATE
50 lbs./hect (17,000 sq. ft. (0.41 acres) with 1,250 lbs. N/1,000 sq. ft. at the LOW RATE
50 lbs./hect (15,100 sq. ft. (0.34 acres) with 1,500 lbs. N/1,000 sq. ft. at the MEDIUM RATE
50 lbs./hect (13,100 sq. ft. (0.28 acres) with 1,750 lbs. N/1,000 sq. ft. at the HIGH RATE

SPREADER	GROUND SPEED	WIDTH OF COVERAGE	SPREADER SETTINGS		
			LIGHT RATE 2.2 lbs/1,000 sq. ft.	MEDIUM RATE 3.3 lbs/1,000 sq. ft.	HIGH RATE 3.8 lbs/1,000 sq. ft.
Andersons AccuPro 2000, SR-2000 (cone 6)	3 mph	11 feet	J 3/4	K 1/4	L
Andersons SS-2 Drop	3 mph	overlap wheels	4	4 1/2	5
Scotts R-8, R-8A (cone 6)	3 mph	11 feet	I 1/2	J 1/4	K
Lesco 020030 (pattern 0.25)	3 mph	10 feet	D	D 1/2	E
Lesco 705508 (pattern 0.25)	3 mph	10 feet	10	11	12
Lely Models WTR, WFR, HR, 1250 (PTO at 450 rpm) Pattern III-C	4.5 mph	34 feet	4 1/4	5	5 1/4
Vicon (03 Series)	4.5 mph	30 feet	18	21	23
					25

SGN 150
Net Wt. 50 Lbs. (22.68 kg)



0 31865131422 3
APT4650
F9 (APTBKPGRNB)