

SPECIMEN LABEL



BREAK-DOWN™

Antifoaming/Defoaming Agent

Principal Functioning Agents

Hydrophobic silica, mineral oil.....	32.7%
Constituents Ineffective.....	67.3%
Total.....	100.0%

All ingredients are exempt from the requirements of a tolerance under 40 CFR 180.

CA Reg. No. 45989-50025

HARMFUL IF SWALLOWED
KEEP OUT OF REACH OF CHILDREN
CAUTION

First Aid

Call a poison control center or doctor immediately for treatment advice.

If swallowed: Have person sip a glass of water to swallow. Do not induce vomiting unless told to by a poison control center or doctor. Do not give anything by mouth to an unconscious person.

If on skin or clothing: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes.

If inhaled: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible.

If in eyes: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after first 5 minutes, then continue rinsing eye. Have the product container with you when calling a poison control center or doctor or going for treatment.

Storage and Disposal

Storage: Keep this product from freezing and do not store in temperatures above 120° F. Do not contaminate water, food or feed by storage or disposal. Store in a cool and dry place. Keep container and contents away from flames, sparks, heat or other ignition sources.

Spills or Leaks: In the event of spillage or leakage surface areas will be slippery. Soak up the material with an absorbent clay, sand, sawdust or other absorbent material. Scrape away and dispose of in accordance with local regulations.

Container Disposal: Do not reuse empty container. Triple rinse or equivalent after use. Recycling decontaminated containers is the best option of disposal.

General Information

Break-Down is a fast active, nonionic, silicone defoaming agent in a reverse emulsion oil-based carrier. Break-Down is a food grade product designed to prevent or eliminate foam in a variety of applications. The use of Break-Down can prevent and suppress foam in spray mixtures and aquatic use sites.

Directions For Use

For foam reduction while mixing spray solutions, add Break-Down at a rate of 1 to 2 ounces per 100 gallons of spray solution. Water hardness, temperature or tank mix ingredients may require an adjustment up or down in rate.

For preventative defoaming, add Break-Down to a partially water-filled tank first and agitate briefly before adding other products to the water then add remaining water and begin tank mix agitation. Urea water solution may require the higher use rate range for this product.

If foaming re-develops after the tank mix level drops, stop agitation and add an additional 1 oz. of Break-Down.

Notice-Read Carefully

Limited Warranty and Conditions of Sale

In no event shall KALO, Inc., manufacturer or seller be liable for special, incidental, or consequential damages, or for damages in their nature of penalties relating to the goods sold. KALO, Inc., manufacturer or seller shall not be liable to buyer or user by way of indemnification to customers of buyer, if any, or for any damages or sums of money, claims or demands whatsoever, resulting from or by reason of, or rising out of the misuse, or failure to follow label warnings or instructions for use, of the goods sold by KALO, Inc., manufacturer or seller. Buyer or users exclusive remedy and KALO, Inc., manufacturer or sellers total liability shall be for damages not exceeding the cost of the product.

Warranty Disclaimer

The goods sold to you by this agreement are furnished as is by KALO, Inc., manufacturer, or seller, and are subject only to the manufacturer's warranties if any, which appear on the labels of the products. KALO, Inc., the manufacturer or seller, make no other warranties, guarantees or representations of any kind to buyer or user, either expressed or implied or by usage of trade, statutory or otherwise, with regard to the product sold, included but not limited to merchantability, fitness for a particular purpose, use or eligibility of the product for any particular trade usage. Ineffectiveness, or other unintended consequences may result because of such factors as the presence or absence of other materials used in combination with the goods, or the manner of use or application, or atmospheric conditions, all of which are beyond the control of KALO, Inc., manufacturer or seller. In no case shall KALO, Inc., manufacturer or seller, be liable for consequential, special or indirect damages resulting from the use or handling of this product. The buyer or its customers shall assume all such risks. Tests have not been carried out under all possible use conditions, and KALO, Inc., manufacturer or seller, cannot and do not warrant that the product is compatible with all other chemicals.

The law of the state from which such goods are to be shipped shall govern the validity, interpretations and performance of this agreement with respect to goods delivered. This writing contains all of the representations and agreements between buyer, KALO, Inc., manufacturer and seller, and no person or agent of KALO, Inc., manufacturer or seller has any authority to make any representation or warranty or agreement relating in any way to the goods.



KALO, Inc. Overland Park, KS 66213 800-255-5196 www.kalo.com
Break-Down is a trademark of KALO, Inc. 3/23/09