

Material Safety Data Sheet

J. R. Simplot Company

AgriBusiness

M78003

Trade Name: PHT Ad-Wet 90
Registration No: 7001-03002 (Washington)

SECTION 1

CHEMICAL PROPERTIES AND COMPANY INFORMATION

Manufacturer or Formulator: J.R. Simplot Company
P.O. Box 70013
Boise, ID 83707
Emergency Phone - Chemtrec: 1-800-424-9300

Product Name: PHT Ad-Wet 90
Common Name: Ad-Wet 90
Chemical Type: Adjuvant

SECTION 2

COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name and Synonyms	C.A.S. No.	Chemical Formula	WT% Hazardous	TLV	PEL
Isopropyl Alcohol	67-63-0	CH ₃ CHOHCH ₃	<20%	200 ppm (400 ppm STEL)	400 ppm
Ethanol, 2, 2-Oxybis	111-46-6	(2CH ₂ OH) ₂ O	<20%	Not established	Not established
Ethylene Oxide	75-21-8	(CH ₂) ₂ O	<1ppm	1 ppm	1 ppm (5 ppm STEL)

SECTION 3

HAZARDS IDENTIFICATION

Ingestion: Harmful if swallowed. Can enter lungs and cause damage. May cause dizziness and drowsiness. Aspiration hazards, if swallowed. This product is not to be used in food, cosmetic or potable water applications. Product contains ethylene glycol and/or diethylene glycol, which can be toxic if swallowed.

Inhalation: Excessive vapors or mist in unusually high concentrations generated from spraying, heating the material or as from exposure in poorly ventilated areas may cause aggravation to the nose and throat, headache, nausea and drowsiness.

Eye Contact: May cause severe aggravation.

Skin Contact: Short and long term exposure can aggravate and cause redness and swelling.

Effects of Overdose: Overexposure to any chemical may result in enhancement or pre-existing adverse medical conditions and allergic reactions.

SECTION 4

FIRST AID MEASURES

Ingestion: If swallowed, give two large glasses of water and get medical attention immediately. Do not induce vomiting. Do not give anything by mouth to an unconscious person.

Inhalation: If overcome by vapors, remove to fresh air. Keep individual calm. If breathing has stopped, give artificial respiration, and immediately seek medical help.

Eyes: In case of contact with eyes, immediately flush with water for at least 15 minutes and then get medical attention. Remove contact lenses if present.

Skin: Immediately flush with continuous flow of water for at least 15 minutes. Remove contaminated clothing and shoes immediately. Thoroughly wash clothing before reuse.

SECTION 5

FIRE FIGHTING MEASURES

Extinguishing Media: Alcohol foam, CO₂ or dry chemicals. Water may be ineffective.

Special Fire Fighting Procedures: Use water spray to cool fire-exposed surfaces and to protect personnel. Respiratory protection required for fire fighting personnel. Stay upwind if possible. Cool exposed tanks with water.

Unusual Fire and Explosion Hazards: WARNING: This product is COMBUSTIBLE. Reacts violently with oxidizers. Moderate explosiveness when exposed to heat or flame.

SECTION 6

ACCIDENTAL RELEASE MEASURES

Environmental Precautions: Will produce BOD. Air pollution hazard: low. Will biodegrade at moderately fast-rate to acetone. Major species threatened: terrestrial life.

Steps to be taken in case material is released or spilled: Keep public away. Shut off source if possible to do so without hazard. Eliminate sources of ignition. Warn occupants of downwind areas of explosion hazard. Evacuate area. Prevent liquid from entering sewers, water sources of low areas.

SECTION 7

HANDLING AND STORAGE

Precautions to be taken in handling and storing: Store away from heat or open flame and oxidizing materials. Do not contaminate water, food or feed by storage or disposal.

SECTION 8

EXPOSURE CONTROLS/PERSONAL PROTECTION

Ventilation Protection: Adequate ventilation.

Respiratory Protection: Use approved respiratory protection such as air-supplied mask if in enclosed area.

Protective Clothing: Clean work clothing, chemical resistant gloves.

Eye Protection: Chemical splash goggles.

Other: No smoking or open flames. Wash hands thoroughly after handling product and before eating, drinking or using tobacco products.

SECTION 9

PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point:	Unknown	Solubility in Water:	Soluble
Specific Gravity:	1.06 @ 68°F SCC	% Volatiles (by volume):	Unknown
Flashpoint:	> 120°F	Vapor Pressure, mm Hg:	Unknown
pH:	6.0 - 7.0	Reaction with Water:	Not applicable
Appearance:	Clear amber liquid. Mild alcohol odor.	Density:	8.84 lbs/gallon
Extinguishing Media:	Alcohol foam, CO ₂ , dry chemical.		

Trade Name: PHT Ad-Wet 90
Registration No: 7001-03002 (Washington)

M78003

SECTION 10

STABILITY AND REACTIVITY

Stability (Normal Conditions): Stable
Conditions to Avoid: Heat and open flame, sparks, oxidizing materials.
Incompatibility (Material to Avoid): Alkylene oxides, acid anhydrides, inorganic acids, organic acids, phosphorous trichloride, aldehydes, monomers, polymerizable esters, hydrogen with palladium and storing this product in aluminum vessels.
Hazardous Decomposition Products: No unusual products of combustion.
Hazardous Polymerization: Will not occur

SECTION 11

TOXICOLOGY INFORMATION

Ingestion: Acute Oral (rat): LD₅₀ 5840 mg/kg. Moderate toxicity via oral and ipr routes. The single LD for a human adult is approximately 250 ml². Oral-HMN TDLO: 15710 mg/kg; CNS> Oral-man LDLO: 8600 mg/kg.
Inhalation: IHL-HMN TCLO: 400 ppm; IRR.
Skin Absorption: Skin--rabbit: LD₅₀: 13 gm (13000 mg/kg).

SECTION 12

ECOLOGICAL INFORMATION

None listed.

SECTION 13

DISPOSAL CONSIDERATIONS

Waste Disposal Procedures: Wastes resulting from this product may be disposed of on site or at an approved waste facility.

SECTION 14

TRANSPORT INFORMATION

Shipping name:	Combustible Liquid, N.O.S.	Packaging Group:	III
Hazard Class:	Combustible liquid	C.A.S. Number:	See "Ingredients"
Reportable Quantity (RQ):	None	D.O.T. Number:	NA 1993
Labels Required:	None	Haz Waste No:	D001
Placard:	Combustible	EPA Regist No:	7001-03002 Washington

SECTION 15

REGULATORY INFORMATION

Carcinogenicity: by IARC?: Yes () No (X) by NTP?: Yes () No (X)
Ethylene Oxide is a known human carcinogen. This product contains <1ppm ethylene oxide.

CERCLA Reportable Quantity

Glycol Ethers (fraction of product matching EPA definition): 0.61-1.99% in product, Reportable Quantity = 1 lb.
Residual Ethylene Oxide: <0.001% in product, Reportable Quantity = 10 lbs.

Section 302/304 Extremely Hazardous Substances

Residual Ethylene Oxide (Range % <0.001) below reportable concentrations.

Section 311/312 Hazard Categories

This product has been reviewed according to the EPA "Hazard Categories" promulgated under Section 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following category: *Immediate Health Hazard.*

Section 313 Reportable Ingredients

Glycol ethers (CAS Number: *Mixture*) concentration 0.61-1.99%.

WARNING! This product contains a detectable amount of ethylene oxide, which is known to the State of California to cause cancer and/or reproductive toxicity.

Ethoxylated products may contain residual amounts of ethylene oxide (EO) which can accumulate in container headspace and be released in the ambient environment. This process is enhanced when the product is agitated, as during tank car loading and unloading, and blending operations. Ethylene oxide causes tumors in laboratory animals. The OSHA Permissible Exposure Limit (PEL) for EO is 1 ppm for an eight-hour time weighted average exposure. The standard regulates occupational exposure to EO from all sources, including products containing EO. It is the responsibility of the employer to comply with the OSHA ethylene oxide standard 29 CFR 1910.1047.

SECTION 16

OTHER INFORMATION

Flash Point (Test Method):	120°F (49°C) (PMCC)	Flammable Limits	LOWER	UPPER
Autoignition Temperature:	750°F (399°C)	(% BY VOLUME)	N/A	N/A

Hazard Rating (N.F.P.A.): Health: 1 Fire: 1 Reactivity: 0 Specific: Not applicable
This N.F.P.A. rating is a recommendation by the manufacturer using the guidelines or published evaluations prepared by the National Fire Protection Association (N.F.P.A.).

MSDS Version Number: 6 (revisions to sections 1, 2, 3, 4, 8, 9, 14, 15, and 16)

Disclaimer: This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. **NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE CONCERNING THE INFORMATION HEREIN PROVIDED.** It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use. We do not accept liability for any loss or damage that may occur from the use of this information nor do we offer warranty against patent infringement.

Reviewed by: The Environmental Health & Safety Department
December 2010 (208) 389-7394