Material Safety Data Sheet J. R. Simplot Company AgriBusiness

Trade Name: PHT Kicker Ultra Dry M77338

Registration No: None

SECTION 1 CHEMICAL PRODUCT AND COMPANY INFORMATION

Manufactured For:

J.R. Simplot Company

Product Name: PHT Kicker Ultra Dry

R.O. Box 70040

P.O. Box 70013 Common Name: Kicker Ultra Dry
Boise, ID 83707 Chemical Type: Dry water-soluble adjuvant

Emergency Phone - Chemtrec: 1-800-424-9300

SECTION 2 COMPOSITION INFORMATION

Chemical Name and Synonyms C.A.S. No. Chemical Formula WT% TLV PEL

None listed 15 mg/m³ nuisance dust 15 mg/m³ nuisance dust

SECTION 3 HAZARDS IDENTIFICATION

Ingestion: May cause considerable gastric upset, ulceration or hemorrhage of the gastrointestinal tract and diarrhea. Systemic ammonia

poisoning is possible if sufficient absorption occurs.

Not an expected route of exposure. May cause discomfort.

Eye Contact: Listed as route of entry.
Skin: Listed as route of entry.

Inhalation:

SECTION 4 FIRST AID MEASURES

Ingestion: If victim is conscious and alert, give 1-2 glasses of water to drink. Do not give anything by mouth to an unconscious person.

Seek medical attention. Do not leave victim unattended.

Inhalation: If respiratory discomfort or distress occurs, remove victim to fresh air. Seek medical attention if respiratory discomfort or

distress continues.

Eyes: Hold eyelids open and flush with a steady, gentle stream of water for at least 15 minutes. Seek medical attention.

Skin: In case of contact, immediately wash with plenty of soap and water for at least 5 minutes. Seek medical attention. Remove

contaminated clothing and shoes. Clean contaminated clothing and shoes before re-use.

Note to Physician: All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to

the possibility that overexposure to materials other than this product may have occurred. Treat symptomatically. No specific

antidote available.

SECTION 5 FIRE FIGHTING MEASURES

Extinguishing Media: Water fog, foam, CO₂, or dry chemical.

Special Fire Fighting Procedures: Firefighters should wear NIOSH/MSHA approved self-contained breathing apparatus and full protective

clothing. Special procedures should not be necessary.

Unusual Fire and Explosion Hazards: Dust suspended in air creates explosion hazard. When heated to decomposition, hydrogen cyanide, carbon

monoxide and ammonia may be emitted.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Steps to be taken in case material is released or spilled:

Sweep, vacuum, or absorb with an inert absorbent for collection in an approved recovery drum for disposal. Wash area with water. Collect wash water for disposal. Always follow federal, state and local regulations regarding waste disposal.

SECTION 7 HANDLING AND STORAGE

Precautions to be taken in handling and storing:

Avoid breathing vapors and mists. Avoid prolonged contact with skin and eyes. Do not store, use, and/or consume foods, beverages, tobacco products, or cosmetics in areas where this material is stored. Wash hands and face carefully before eating, drinking, using tobacco, applying cosmetics or using the toilet. Store in tightly closed original-labeled

containers. Store in a dry, well-ventilated area away from ignition sources.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

These recommendations provide general guidelines for handling this product. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application.

Ventilation Protection: None listed.

Respiratory Protection: Use NIOSH/MSHA approved respirator when exposure limits have been exceeded or are expected.

Protective Clothing: Gloves and suitable long-sleeved clothing (shirts and pants).

Eye Protection: Chemical safety glasses with side shields or splash-proof goggles when using this product is recommended. An

emergency eye wash and safety shower should be accessible to the work area.

PHT Kicker Ultra Dry M77338 Trade Name:

Registration No: None

> PHYSICAL AND CHEMICAL PROPERTIES **SECTION 9**

Flashpoint: Difficult to burn or continue burning Solubility in Water: Soluble Density: 52-57 lbs/ft3 % Volatiles (by volume): Not listed Flashpoint: Non-flammable Vapor Pressure, mm Hg: Not applicable pH: No data Reaction with Water: Not listed.

Appearance: Free-flowing white granules; slight chemical odor.

Extinguishing Media: Use media suitable for extinguishing source of fire.

SECTION 10 STABILITY AND REACTIVITY

Stability (Normal Conditions): Stable

Conditions to Avoid: Heat, open flame, spark.

Incompatibility (Material to Avoid): Strong oxidizers, bases, chlorates and nitrates.

Temperatures above 282°C causes release of ammonia and sulfur trioxide. **Hazardous Decomposition Products:**

Hazardous Polymerization: Will not occur

> **SECTION 11 TOXICOLOGY INFORMATION**

None established.

SECTION 12 ECOLOGICAL INFORMATION

None listed.

SECTION 13 DISPOSAL CONSIDERATIONS

Waste Disposal Procedures: Since empty packaging contains residues of the product, all labeled hazard precautions should be observed.

Always follow federal, state and local regulations regarding waste disposal.

SECTION 14 TRANSPORT INFORMATION

Shipping name: Not regulated by DOT

Hazard Class: None C.A.S. Number: None Reportable Quantity (RQ): None D.O.T. Number: None Labels Required: None Haz Waste No: None Placard: None **EPA Regist No:** None

SECTION 15 REGULATORY INFORMATION

SARA 302/311/312 Hazard Categories: 302 - acrylamide (impurity) > 0.1%

304 CERCLA/313 Reportable Ingredients: 313 - sulfuric acid diammonium < 100%, 304 - acrylamide (impurity) > 0.1% **TSCA Status:** All chemical substances in this product are listed in the TSCA inventory.

SECTION 16 OTHER INFORMATION

UPPER Flash Point (Test Method): LOWER Not applicable Flammable Limits **Autoignition Temperature:** Not applicable (% BY VOLUME) N/A N/A

MSDS Version Number: 2

Disclaimer: This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE CONCERNING THE INFORMATION HEREIN PROVIDED. It is the user's responsibility to satisfy themselves as to the suitability and completeness of such information for their own particular use. We do not accept liability for any loss or damage that may occur from the use of this information nor do we offer warranty against patent infringement.

> Reviewed by: Environmental, Health, & Safety Department May 2007 (208) 389-7394