

Material Safety Data Sheet
J. R. Simplot Company
AgriBusiness

M77333

Trade Name: PHT Persist® Ultra
Registration No: None

SECTION 1 CHEMICAL PRODUCT AND COMPANY INFORMATION

Manufactured For: Plant Health Technologies
P.O. Box 70013
Boise, ID 83707
Emergency Phone - Chemtrec: 1-800-424-9300

Product Name: PHT Persist® Ultra
Common Name: Emulsifiable Methyl Ether
Chemical Type: Blend of Methyl Esters and Emulsifiers

SECTION 2 COMPOSITION INFORMATION

Chemical Name and Synonyms	C.A.S. No.	Chemical Formula	WT%	TLV	PEL
Methyl Esters	not listed	not listed	80	not listed	not listed
Nonionic Surfactants	not listed	not listed	8	not listed	not listed
Glycol Ethers	not listed	not listed	8	not listed	not listed
N-Butanol	not listed	not listed	4	50 ppm (152 mg/m ³)	100 ppm (300 mg/m ³)
Ethylene Oxide	75-21-8	not listed	trace	1 ppm (1.8mg/m ³)	1 ppm/5 ppm
Acetaldehyde	75-07-0	not listed	trace	none listed	100 ppm (180 mg/m ³)
1,4-Dioxane	123-91-1	not listed	trace	not listed	not listed

SECTION 3 HAZARDS IDENTIFICATION

Ingestion: May be harmful if swallowed.
Inhalation: May cause discomfort to the nose, throat and respiratory system. May cause blurred vision, headache, dizziness and drowsiness.
Eye Contact: Contact with eyes may cause aggravation or burning.
Skin Contact: Contact with skin may cause aggravation or burning.
Effects of Overdose: None listed.

SECTION 4 FIRST AID MEASURES

Ingestion: If victim is conscious and able to swallow, quickly have victim drink water or milk to dilute. DO NOT give sodium bicarbonate, fruit juices or vinegar. Never give anything by mouth if victim is unconscious or having convulsions. Induce vomiting only if advised by a physician or poison control center. Call physician or poison control center immediately.
Inhalation: Immediately remove victim to fresh air. If victim has stopped breathing, give artificial respiration. Take care that rescuer does not become contaminated.
Eyes: Immediately flush eyes with plenty of cool water for at least 15 minutes. Do not let victim rub eyes. Get medical attention immediately.
Skin: Immediately flush skin with plenty of water while removing contaminated clothing. Get medical attention immediately. Wash contaminated clothing before reuse.

SECTION 5 FIRE FIGHTING MEASURES

Extinguishing Media: Dry chemical, water spray, water fog, CO₂, foam and sand/earth.
Special Fire Fighting Procedures: Individuals should perform only those fire fighting procedures for which they have been trained. Use water spray, dry chemical, foam or carbon dioxide. Use water to keep fire-exposed containers cool. If a spill or leak has not ignited, use water spray to disperse the vapors. Water spray may be used to flush spills away from the fire and to dilute spills to non-flammable mixtures.
Unusual Fire and Explosion Hazards: Fire fighters should wear self-contained breathing apparatus in the positive-pressure mode with a full face piece when there is a possibility of exposure to smoke, fumes or hazardous decomposition products.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Steps to be taken in case material is released or spilled:
Avoid uncontrolled releases of this material. Where spills are possible, a comprehensive spill response plan should be developed and implemented. Wear appropriate respiratory protection and protective clothing as described in Section 8. Contain spilled material. Transfer to secure containers. Where necessary, collect using absorbent media. In the event of an uncontrolled release of this material, the user should determine if the release is reportable under applicable laws and regulations. All recovered material should be packaged, labeled, transported and disposed or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Avoid land filling of liquids. Reclaim where possible.

SECTION 7 HANDLING AND STORAGE

Precautions to be taken in handling and storing:
Protect against physical damage. Detached or outside storage is preferred. Inside storage should be in standard flammable liquids storage room or cabinet. All ignition sources should be eliminated. Smoking should be prohibited in storage areas. Electrical installations should be in accordance with the National Electrical Code. Frequent careful leakage inspection should be done. Automatic sprinkler system should be provided. Isolate from oxidizers, chemicals capable to spontaneous heating, materials reacting with air or moisture to liberate heat, ignition sources and explosives.

Trade Name: PHT Persist® Ultra
Registration No: None

M77333

SECTION 8

EXPOSURE CONTROLS/PERSONAL PROTECTION

Ventilation Protection: Adequate ventilation.
Respiratory Protection: Where exposure is likely to exceed acceptable criteria, use approved respiratory equipment.
Protective Clothing: Wear gloves and protective clothing which are impervious to the product for the duration of anticipated exposure if there is potential for prolonged or repeated skin contact.
Eye Protection: Chemical safety goggles should be worn whenever there is the possibility of contact with eyes. Spectacle-type safety glasses do not provide satisfactory protection. An eyewash fountain should be readily available.
Other: None listed.

SECTION 9

PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point:	No data available	Solubility in Water:	Disperable
Specific Gravity:	No data available	% Volatiles (by volume):	2
Flashpoint:	150°F (65°C)	Vapor Pressure, mm Hg:	No data available
pH:	5-7	Reaction with Water:	Not listed
Appearance:	Clear liquid.	Evaporation Rate:	No data available
Extinguishing Media:	Use media suitable for extinguishing source of fire.	Vapor Density:	Greater than 1

SECTION 10

STABILITY AND REACTIVITY

Stability (Normal Conditions): Stable under normal conditions.
Conditions to Avoid: Keep away from heat and flames. Avoid contact with oxidizing materials.
Incompatibility (Material to Avoid): Keep away from oxidizing materials.
Hazardous Decomposition Products: Decomposition may produce carbon monoxide and carbon dioxide.
Hazardous Polymerization: Not likely to occur.

SECTION 11

TOXICOLOGY INFORMATION

None listed.

SECTION 12

ECOLOGICAL INFORMATION

None listed.

SECTION 13

DISPOSAL CONSIDERATIONS

Waste Disposal Procedures:

SECTION 14

TRANSPORT INFORMATION

Shipping name:	Combustible Liquid, N.O.S. (contains butanol), Combustible, NA1993, P.G. III		
Hazard Class:	Combustible	C.A.S. Number:	See "Ingredients"
D.O.T. Number:	NA1993	Labels Required:	Combustible
Haz Waste No:	None	EPA Regist No:	None
Placard:	Combustible (for containers > 119 gal capacity)		
Reportable Quantity (RQ):	ethylene oxide (10#), 1,4-dioxane (100#), acetaldehyde (1,000#), n-butanol (5,000#)		

SECTION 15

REGULATORY INFORMATION

Carcinogenicity: by IARC?: Yes () No (X) by NTP?: Yes () No (X)

SARA Title III Section 313 – contains n-butanol and glycol ethers.

SECTION 16

OTHER INFORMATION

Flash Point (Test Method):	Pensky Martin closed cup	Flammable Limits	LOWER	UPPER
Autoignition Temperature:	Not applicable	(% BY VOLUME)	N/D	N/D

MSDS Version Number: 2

Disclaimer: This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. **NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE CONCERNING THE INFORMATION HEREIN PROVIDED.** It is the user's responsibility to satisfy themselves as to the suitability and completeness of such information for their own particular use. We do not accept liability for any loss or damage that may occur from the use of this information nor do we offer warranty against patent infringement.