Material Safety Data Sheet

J. R. Simplot Company AgriBusiness

Trade Name: Sulfuric Acid Desiccant

Registration No: 8917-18

SECTION 1 CHEMICAL PRODUCT AND COMPANY INFORMATION

Manufacturer or Formulator:J.R. Simplot CompanyProduct Name:Sulfuric Acid DesiccantP.O. Box 912Common Name:Sulfuric Acid, Oil of Vitriol

Pocatello, ID 83204 Chemical Type: Inorganic Acid

Emergency Phone - Chemtrec: 1-800-424-9300

COMPOSITION/INFORMATION ON INGREDIENTS **SECTION 2 PEL Chemical Name and Synonyms** C.A.S. No. **Chemical Formula** WT% TLV Hazardous H_2SO_4 1 mg/M³ 1 mg/M³ 8 Hr TWA Sulfuric Acid 7664-93-9 93.5 Non-hazardous Water 7732-18-5 H_2O Not listed Not listed 6.5

SECTION 3 HAZARDS IDENTIFICATION

Ingestion: Moderately toxic. Corrosive to the mouth, throat and stomach. May cause gastrointestinal disturbances. Symptoms may include

salivation, irritation, throat burns, nausea, abdominal pains, vomiting and diarrhea.

Inhalation: Highly toxic. May cause respiratory tract irritation, throat burns, constriction of the windpipe, severe pulmonary edema and death.

May also cause inflammation of the stomach, bronchitis, and tooth erosion. Exposure may cause symptoms similar to those listed

M16021

under "Ingestion."

Extremely irritating and corrosive. Direct contact may cause conjunctivitis, corneal ulceration and permanent injury.

Skin Absorption: May destroy the epidermis and penetrate some distance into the skin and subcutaneous tissues and cause necrosis. Ulceration of

the skin.

Skin Contact: May cause irritation or burns on skin. Prolonged contact may cause severe, deep burns to tissue; very corrosive effects. May

cause dermatitis, ulceration. Burns may not become symptomatic for several hours after contact.

Effects of Overdose: LOCAL: Conjunctivitis, corneal necrosis, dermatitis, skin burns, ulceration. RESPIRATORY: Irritation of the nose and throat,

laryngeal edema, bronchitis, pneumonia, pulmonary edema. GASTROINTESTINAL: Dental erosion, shock, anuria, burning in mouth, throat and abdomen; nausea, vomiting of blood and eroded tissue, perforation of gastrointestinal tract, albumin, blood and

casts in urine.

SECTION 4 FIRST AID MEASURES

Emergency and First Aid Procedures: Treatment is symptomatic and no specific antidotes are known.

Ingestion: Rinse mouth with large amounts of water DO NOT INDUCE VOMITING. Drink large quantities of milk mixed with egg whites or if

this is not available, water. Do not give anything by mouth to an unconscious person.

Inhalation: Remove person from exposure area to fresh air and support breathing. Seek immediate medical attention.

Eyes: IMMEDIATELY flush eyes with fresh running water for 15-20 minutes. Do not wait for symptoms to develop. Get medical attention immediately.

immediately.

Skin: Give continuous flow of water to wash material off body. Remove contaminated clothing (under a shower if possible) and subject

patient to deluge-type shower, if possible. Treat for shock. Prompt medical consultation is essential.

Note to Physician: Probable mucosal damage may contraindicate the use of gastric lavage. Avoid alcohol. Inhalation - Patient should be observed for

latent pulmonary edema for at least 30 hours.

SECTION 5 FIRE FIGHTING MEASURES

Extinguishing Media: Fires involving small amounts of combustibles may be smothered with suitable dry chemicals. Use water on

combustibles in vicinity of this material but use care, as water applied directly to their acid results in evolution of

combustibles in vicinity of this heat and causes splattering.

Special Fire Fighting Procedures: Avoid any contact with acid. Wear full protective rubber clothing, gloves, boots, wear self-contained breathing

apparatus.

Unusual Fire and Explosion Hazards: Not flammable but highly reactive and can cause ignition by contact with combustible materials. Reacts violently

with water and organics. May release explosive hydrogen gas inside storage tanks, drums, tank cars, and tank trucks. This is a very powerful acidic oxidizer which can ignite or even explode on contact with many materials; i.e., acetic acid, acetone cyanhydrin, (acetone + HNO₃), (acetone + $K_2Cr_2O_7$), acetonitrile, acrolein, acrylonitrile, (acrylonitrile + H_2O), (alcohols + H_2O_2), allyl alcohol, allyl chloride, NH $_4OH$, 2-amino ethanol, NH $_4$ triperchromate, aniline, (bromates + metals, BrF $_5$, n-butyraldehyde, carbides, CoHC $_2$, chlorates, (metals + chlorates), CIF $_3$, chlorosulfonic acid, Cu $_3N$, diisobutylene, (dimethyl benzylcarbinol + H_2O_2), epichlorohydrin, ethylene cyanhydrin, ethylene diamine, ethylene glycol, ethylene imine, fulminates, HCl, H_2 , IF $_7$ (indene + HNO $_3$ + glycerides, p-nitroluene, perchlorates, HClO $_4$, (C_6H_6 + permanganates), pentasilver trihydroxydiamino phosphate, (I-phenyl-2-methyl propyl alcohol + H_2O_2), P, P(OCN) $_3$, picrates, potassium-tert-butoxide, KClO $_3$, KMnO $_4$, (KMnO $_4$ + KCl), KMnO $_4$ + H_2O) beta-propiolactone, RbHC $_2$, propylene oxide, pyridine, NA, Na $_2CO_3$, NaOH, steel, styrene

monomer, water, vinyl acetate, (HNO₃ + toluene).

SECTION 6 ACCIDENTAL RELEASE MEASURES

Environmental Precautions: No information available; however, Sulfuric Acid has a reportable quantity of 1000 lbs. and, in the event of an accidental release, should be kept out of all watercourses and bodies of water. Do not contaminate any watercourse or body of water by direct application, cleaning of equipment or disposal.

Steps to be taken in case material is released or spilled:

Treat with extreme caution. Zone off contaminated area. Dike area with sand or earth. Acid may be neutralized with soda ash or lime. Neutralization or dilution of strong Sulfuric Acid will **ALWAYS** be accompanied by a very strong chemical reaction with release of heat and possible splattering of the acid. Organic or combustible materials such as sawdust or rags should never be used to soak up spills. Wear full protective clothing (acid protective slicker suit).

M16021 **Trade Name:** Sulfuric Acid Desiccant

8917-18 Registration No:

SECTION 7 HANDLING AND STORAGE

Precautions to be taken in handling and storing:

Do not contaminate water, food, or feed by storage or disposal. Contents may be under pressure of explosive hydrogen gas. Keep away from heat, sparks and flame. Do not add water to container because of violent reactions. When diluting always add acid to water slowly, never the reverse. Protect against physical damage and water. Wear full protective rubber clothing and rubber gloves and boots, acid hood, and full face shield when loading or unloading tank trucks or railway cars. If exposure is low, acid gas canister may be satisfactory or a self-contained breathing apparatus in the pressure demand mode or a supplied air respirator. Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. In any event always wear eye protection

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Ventilation Protection: Maintain adequate ventilation at all locations where acid is handled. Store in the open or in well ventilated buildings or sheds.

Respiratory Protection: Depends on type of exposure, can range from none to full protection. Self-contained breathing apparatus, or positive

pressure hose mask, or air-line supplied with clean compressed air. Check with respirator manufacturer to determine the

appropriate type of equipment for a given application.

Applicators and other handlers must wear: coveralls over long-sleeved shirt and long pants, waterproof gloves, chemical-**Protective Clothing:**

resistant footwear plus socks, protective eyewear, chemical-resistant headgear for overhead exposure, chemical-resistant apron when cleaning equipment, mixing or loading, and a dust/mist filtering respirator (MSHA/NIOSH approval number prefix TC-21C). When loading or unloading trucks or cleaning out tanks or towers, wear acid resistant slicker suit, rubber clothing

with rubber hood or broad soft hat, rubber apron, rubber gloves, rubber boots, and full face shield.

Suit Material Performance: (suggested by E.P.A.--user should determine by specific use)

> Butyl.....Poor Butyl/Neoprene..... Good CPE Excellent

Chlorobutyl......Good Neoprene.....Good

Eye Protection: Wear chemical safety goggles and face shield. Do not wear contact lenses when working with this substance. Have eye

baths readily available where eye contact can occur.

Safety shower and eyewash fountain checked daily in area. Other:

PHYSICAL AND CHEMICAL PROPERTIES **SECTION 9**

Boiling Point: 530°F Solubility in Water: Complete (Exothermic) Specific Gravity: 1.84 @ 60°F % Volatiles (by volume): 100% @ 644°F Flashpoint: Non-flammable. It may cause ignition on Vapor Pressure, mm Hg: 1 @ 294°F

contact with combustible liquids or solids. **Melting Point:** -31° to 51°F Less than 1.0 Reaction with Water: VIOLENT

pH:

Appearance: Clear, colorless to cloudy liquid **Extinguishing Media:** Dry chemicals or carbon dioxide.

STABILITY AND REACTIVITY **SECTION 10**

Stable Stability (Normal Conditions):

Conditions to Avoid: High temperature, organic materials, powdered metals, and other combustible materials.

Incompatibility (Material to Avoid): Water and most common metals, organic materials, carbides, chlorates, fulminates, nitrates, picrates, powdered

metals, other combustible materials and strong oxidizing agents. Attacks many metals, releasing hydrogen. Acetic acid, acetone cyanohydrin, acetone and nitric acid and styrene monomer, vinyl acetate, nitric acid and

Hazardous Decomposition Products: Hydrogen gas and hazardous fumes of SO_x.

Hazardous Polymerization: Will not occur.

TOXICOLOGY INFORMATION **SECTION 11**

Acute Oral Toxicity: LD₅₀ (rat) is greater than 5,000 mg/kg (ppm); not acutely toxic by oral exposure. (TFI Product Testing Results, OECD

Guideline 425) **Acute Inhalation Toxicity:** LC₅₀ (rat, guinea pig) is 18-420 mg/m³; highly toxic by inhalation. (TFI Product Testing Results)

Acute Aquatic Toxicity: Fish 96-hour LC₅₀ is 42-500 mg/L (ppm); daphnia 24-hour EC₅₀: 29-88 mg/L; algae 10 mg/L. Slightly toxic to aquatic

organisms. (TFI Product Testing Results)

ECOLOGICAL INFORMATION SECTION 12

None listed

SECTION 13 DISPOSAL CONSIDERATIONS

If possible, avoid pouring or spraying water directly onto strong Sulfuric Acid. This ALWAYS results in a violent **Waste Disposal Procedures:**

chemical reaction. It is always best to slowly pour the acid into water during disposal operations to avoid the violent reaction and splattering of acid. If water must be sprayed into the acid for dilution, flushing, etc., it should always be done from a distance with proper protective gear. If these wastes cannot be disposed of by use according to label instructions, contact your Environmental Control Agency or the hazardous waste representative at the nearest EPA

Regional Office for guidance.

SECTION 14 TRANSPORT INFORMATION

Proper shipping name: RQ Sulfuric Acid (with more than 51 percent acid), 8, UN1830, P.G. II

Hazard Class: D.O.T. Number: UN1830 Reportable Quantity (RQ): 1000 lbs. - Sulfuric Acid Haz Waste No: D002 Labels Required: Corrosive **EPA Regist No:** 8917-18 Placard: Corrosive **Packaging Group:**

C.A.S. Number: 7664-93-9

Refer to 49 CFR 172.101 Hazardous Materials Table for further provisions, packaging authorizations and quantity limitations.

Trade Name: Sulfuric Acid Desiccant M16021

Registration No: 8917-18

SECTION 15 REGULATORY INFORMATION

Carcinogenicity: by IARC?: Yes () No (X) by NTP?: Yes () No (X)

IARC evaluates occupational exposures to strong, inorganic-acid mists containing Sulfuric Acid in "Group 1", as having carcinogenic potential. However, SULFURIC ACID ITSELF WAS NOT CLASSIFIED AS A GROUP I CARCINOGEN.

This product contains sulfuric acid, CAS No. 7664-93-9, which is subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

SECTION 16 OTHER INFORMATION

Flash Point (Test Method): Not applicable Flammable Limits LOWER UPPER Autoignition Temperature: Not applicable (% BY VOLUME) N/A N/A

Hazard Rating (N.F.P.A.): Health: 3 Fire: 0 Reactivity: 2 Specific: Use no water

This N.F.P.A. rating is a recommendation by the manufacturer using the guidelines or published evaluations prepared by the National Fire Protection Association (N.F.P.A.).

FIREFIGHTING TECHNIQUE

Concentrated vapors of Sulfuric Acid are extremely irritating to the respiratory tract and may cause breathing difficulty. Prevent human exposure to fire, smoke, fumes, or products of combustion. Evacuate nonessential personnel from the fire area. Maintain a safe distance from the fire and storage area because excessive heat may cause tank to rupture. Wear full face, self-contained breathing apparatus and impervious clothing (such as gloves, hood, suits, and rubber boots). Use water spray, dry chemical, foam, carbon dioxide, or halogenated extinguishing agents. If the tank is not leaking, keep cooled using a fog spray nozzle to minimize the reactivity of the water and acid. Under no circumstance should water or other liquid be introduced into acid tanks. Take care not to ignite hydrogen gas which can accumulate inside metal tanks containing acid.

SPECIAL HANDLING

Make sure all personnel involved in the spill cleanup follow good industrial hygiene practices.

A small spill can be handled routinely. Use adequate ventilation or wear an air-supplied respirator to prevent inhalation contact. Wear suitable protective clothing to prevent skin and eye contact. Use the following procedures:

Any leak occurring in pipelines or equipment should be considered an acid leak and treated with extreme caution until the leak is proven not to be an acid leak.

All contaminated areas should be immediately zoned off to avoid personnel exposure to the acid spray or stream.

Adjust all appropriate valves to isolate the system and stop further leakage.

Soda ash or lime should be spread around to neutralize any remaining acidity on the surface of the ground or concrete pad. The contaminated area should be covered with sand or gravel, and acidity neutralized with soda ash or lime.

Sulfuric Acid leaks, spills or drainings must not come in contact with any acid soluble sulfide wastes (such as in sewers) because of danger of evolving hydrogen sulfide gas.

Large spills should be handled according to the predetermined plan. Part of this plan should include Section V, FIRE FIGHTING MEASURES.

CORROSIVITY TO MATERIALS OF CONSTRUCTION

Weaker strengths of Sulfuric Acid, particularly concentrations below 60° Baume, are highly corrosive to most metals with evolution of hydrogen gas.

STORAGE REQUIREMENTS

The following safety facilities should be readily accessible in all areas where Sulfuric Acid is handled or stored.

SAFETY SHOWERS--with quick opening valves which stay open. Water should be supplied through insulated lines to prevent freeze-ups in cold weather. EYEWASH FOUNTAIN--or other means of washing the eyes with a gentle flow of tap water.

Sulfuric Acid may be safely stored in properly designed bulk storage tanks.

DISPOSAL OF UNUSED MATERIAL

Sulfuric Acid that cannot be used or chemically reprocessed should be disposed of in such a manner that will not adversely affect the environment.

MSDS Version Number: 4 (revisions to Section 11)

Disclaimer: This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE CONCERNING THE INFORMATION HEREIN PROVIDED. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use. We do not accept liability for any loss or damage that may occur from the use of this information nor do we offer warranty against patent infringement.

Reviewed by: The Department of Regulatory Affairs June 2001 (208) 672-2700