Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard 29CFR 1910. Standard must be consulted for specific requirements.

Product: Dyna Flo 0-0-25 17% S

QUICK IDENTIFIER

Common Name: (Used on label and list)

SECTION 1 -							
Manufacturer's Name:	Chemical Dynamics, Inc	C.	Emergency Tele	ephone Number:	1-800-424	1-800-424-9300	
Address:	4206 Business Lane		Other Information	on Calls:	1-813-752	1-813-752-4950	
City, State, and Zip	Plant City, Florida 3356	7	Date Prepare:		8/27/98	8/27/98	
SECTION 2 -	HAZARDOUS IN	IGREDIEN	ITS/IDENTI	TY			
Hazardous Component(s) (d	chemical & common name(s	s)	OSHA PEL ACC	GIH TLV EXPOS	URE LIMITS	CAS NO.	
Potassium Thiosulfate			N/A			10294-66-3	
SECTION 3-	PHYSICAL & CH	IEMICAL	СНАВАСТ	EDISTICS			
Boiling Point:		ific Gravity:	1.472	Vapor Press	sure: N/A		
•	·	•		-			
Vapor Pressure:	N/A Reactiv	ity in Water:	Soluble	Melting P	OIIII: N/A		
Appearance and Odor:	Clear no odor						
SECTION 4-	FIRE & EXPLOS	SION DAT	Ά				
Flash Point:		Method Used:	N/A				
Flammable Limits in Air: Auto-Ignition Temp:		LEL Lower: isher Media:	Non flammable	UEL Up if involved in fire		with	
3			dry chemical; C	O ₂ , water spray o	or foam.		
	This product is non-flan	nmable, and o	loes not support	combustion.			
Procedures:	·						
	Heating of this product	will evolve su	lfur dioxide.				
Explosion Hazards:	<u> </u>						
SECTION 5-	PHYSICAL HAZ	ARDS (RE	= ACTIVITY	ΠΔΤΔ)			
				•			
Stability:	<u> </u>		Unstable	Conditions to Av	void: Excessive	e heat	
Incompatibility Materials to Avoid!:							
Incompati	bility Materials to Avoid					en	
		this solution	n comes in conta	act with acidic ma	aterials.		
Page 2-	Dyna Flo 0-0-25 17% S						
SECTION 5-	PHYSICAL HAZ	ARDS (DI		DATA) Co-	ntinuad		
3ECTION 5-	FITTSICAL HAZ	ארטס (גו	ACTIVITY	DATAJCOI	ııııueu		
Hazardous [Decomposition Products	: Excessive h	neat will result in	Sulfur dioxide fu	ımes.		

Haz	zardous Polymerization: May Occur: Will Not Occur:				
	Conditions to Avoid: Extreme Heat.				
SECTION 6-	HEALTH HAZARDS				
ACUTE:	Mild skin irritant, conjunctivitis, upset stomach and or gastrointestinal symptoms				
CHRONIC:	are temporary. Prolonged skin contact may result in dermatitis (drying) or eczema (itching)				
CARCINOGEN	NTP OSHA				
LISTED IN:	IARC MONOGRAPH X NOT LISTED				
R	OUTES OF ENTRY AND EMERGENCY FIRST AID PROCEDURES				
1. Inhalation:	Move victim to fresh air and perform artificial respiration if necessary. Call				
2. Eyes:	n if symptoms persist. es with running water for 15 minutes.				
Z. Eyes.	riusii eyes witti rutiiliing water tor 13 minutes.				
3. Skin:	Wash with soap and water, remove contaminated clothing.				
4. Ingestion:	Give large amounts of water and INDUCE VOMITING. Call a physician				
	immediately.				
SECTION 7-	SPECIAL PRECAUTIONS AND SPILL/LEAK PROCEDURES				
Precautions to be Taken					
Handling and Storage:	e: Store in cool ventilated place away from fire hazards, excessive heat, flammable				
	or easily oxidizable materials.				
Other Precautions:	Do not allow product to go below 35 degrees. Apply product in open areas.				
Other i recautions.	Keep away from children and pets. Do not contaminate any water sources.				
Steps to be taken in					
case of Release or Spill	Clean at once. Do not allow dry material to come in contact with heat.				
Waste Disposal:	Consult federal, state, and local regulations Flush with water to and collect in a chemical waste disposal. Dispose according				
	to federal, state and local regulations.				
SECTION 7-	CONTROL AND PROTECTIVE MEASURES				
	None required if used in open under normal conditions.				
Respiratory Protection.	Self contained respiratory equipment should be used in the event of a spill.				
Protective Gloves:					
	Goggles or face shield.				
Other Protective					
Clothing or equipment:	Wear clean clothing.				
Hygienic Work Practice	Bath and wash clothes after mission is complete.				
	<u> </u>				