Page 1 of 3 Date of Issue: 01-20-03

Diamond R Fertilizer Co., Inc.

P.O. Box 12489 • Ft. Pierce, FL 34979 • (800) 330-9300

MATERIAL SAFETY DATA

1. PRODUCT IDENTIFICATION

PRODUCT NAME: BALANCE pH
SYNONYMS: Acidifying-Surfactant
CHEMICAL FAMILY: Proprietary Blend

GENERIC DESCRIPTION: NA MOLECULAR WEIGHT: NA

2. HAZARDOUS INGREDIENTS

OSHA REGULATED

 COMPONENT
 CAS. NO
 WT%
 EXPOSURE LIMITS

 Propionic Acid
 79-09-04
 35
 10 ppm / 8 hr. TWA

 15 ppm / 15 min. STEL

The maximum of 1 ppm Ethylene Oxide (EO)(75-21-8) May be present in the product.

The OSHA PEL and ACGIH TLV for EO is 1 ppm.

3. EFFECTS OF OVEREXPOSURE:

EYE: Causes severe eye burns. SKIN: Causes severe skin burns.

INHALATION: Mists or vapors are harmful to respiratory tract.

ORAL: Harmful if swallowed.

The above listed potential effects of overexposure are based on actual data, results of studies performed upon similar compositions, component data and/or expert review of the product. Overexposure to any chemical may result in enhancement of pre-existing adverse medical condition and allergic reactions.

4. EMERGENCY FIRST AID

EYES: Flush immediately with a lot of water for 15 minutes. Get immediate medical attention. SKIN: Remove contaminated clothing, flush with plenty of water. Get medical attention or

contact poison control center immediately.

INHALATION: Remove to fresh air. Apply artificial respiration if necessary. Get immediate medical

attention.

INGESTION: Do not induce vomiting. Drink 2 glasses of water or milk immediately. Get medical

attention immediately. Never give anything by mouth to an unconscious person.

5. REACTIVITY DATA

STABILITY: Stable

CONDITIONS TO AVOID: Excessive heat and open flames.

POLYMERIZATION: Will not occur.

INCOMPATIBILITY: Strong oxidizing agents. Can react with metals, strong bases and amines.

DECOMPOSITION: Carbon dioxide, carbon monoxide.

6. PHYSICAL PROPERTIES

APPEARANCE AND ODOR: Amber to dark brown liquid, Vinegar like

BOILING POINT:

MELTING POINT:

VAPOR PRESSURE (mmg of Hg):

NA

SPECIFIC GRAVITY: 0.997 (+/- .05)

VAPOR DENSITY (AIR=1):
% VOLATILE (BY WGT.%):
EVAPORATION RATE (Butyl A.)r=1):
NA
SOLUBILITY IN WATER:
Soluble

Page 2 of 3 Date of Issue: 01-20-03

7. NFPA HAZARD RATING (National Fire Protection Association)

Fire FIRE: Materials that must be preheated before ignition can occur.

2

Health 3 0 Reactivity HEALTH: Materials which on exposure should cause irritation but

only minor residual injury even if no treatment is given.

Special REACTIVITY: Materials which in themselves are normally stable,

even under fire exposure conditions, and which are not

reactive with water.

8. FIRE AND EXPLOSION HAZARD INFORMATION

FLASHPOINT: >130°F (Pensky-Martens closed cup ASTM D93)

FLAMMABLE LIMITS: Not Available

EXTINGUISHING MEDIA: Foam, Dry Chemical, CO2, Water Spray

FIRE FIGHTING: Use alcohol-type or universal-type foams on larger fires. Smaller fires

should be extinguished with carbon dioxide or dry chemical. Do not use water or foam directly on the fire. Use self-contained breathing apparatus

with fighting any fire in an enclosed area.

UNUSUAL FIRE HAZARD: May be ignited by heat, sparks or flames. Vapors may travel to a source

of ignition and flash back. Containers may explode in heat of fire.

9. SPECIAL PRECAUTIONS

HANDLING AND STORAGE: Keep out of reach of children. Store in cool dry place. Keep in original

container tightly closed. Do not reuse empty container.

OTHER PRECAUTIONS: Do not store with food, feed, or other material to be used or consumed

By humans or animals. Do not contaminate water supplies. Do not store

with materials labeled "Oxidizers" or oxidizing agents.

10. SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: Wear a NIOSH/OSHA approved respirator if necessary. VENTILATION: Normal room ventilation (mechanical) should be satisfactory.

PROTECTIVE GLOVES: Impervious.

EYE PROTECTION: Wear goggles or a face shield. OTHER PROTECTION: Eye wash and safety shower.

11. SPILL OR LEAK PROCEDURES

SPILLS OR RELEASES: Material should be collected and disposed in proper manner. Avoid

Discharge to natural waters as concentrated material is highly toxic to

fish. Wear suitable protective equipment.

WASTE DISPOSAL: Do not contaminate water, food or feed by storage or disposal. Dispose

of in an approved waste disposal facility in accordance with all Federal,

State and Local Regulations.

CONTAINER DISPOSAL: Triple rinse (or equivalent) adding rinse water to application tank. Offer

container for recycling or dispose of in a sanitary landfill or by other

procedures approved by local regulations.

12. REGULATORY INFORMATION

COMPOUNDS WHICH REQUIRE REPORTING UNDER SARA TITLE III

Sara regulated compounds	% Wt	Acute	Chronic	Fire	Reactivity	Pressure	CAS NO.
Propionic Acid	35	ves	no	ves	no	no	79-09-4

Page 3 of 3 Date of Issue: 01-20-03

13. OTHER INFORMATION

WARNING! This product contains a detectable amount of ethylene oxide, which is known to the State of California to cause cancer and/or reproductive toxicity.

Ethoxylated products may contain residual amounts of ethylene oxide (EO) which can accumulate in the container headspace and be released into the ambient environment. This process is enhanced when the product is agitated, as during tank car loading and unloading, and blending operations. Ethylene oxide causes tumors in laboratory animals. The Occupational Safety and Health Administration (OSHA) Permissible Exposure Level (PEL) for EO is 1 ppm for an eight-hour time weighted average exposure. The standard regulates occupational exposure to EO from all sources, including products containing residual EO. It is the responsibility of the employer to comply with OSHA ethylene oxide standard (29) CFR 1910.1047).

The recommendation for safe handling and protection procedures is believed to be generally suitable for the standard uses of this compound. However, each user should identify his intended uses of this material and determine whether they are appropriate. All data included in this document is released as typical values and should not be utilized to determine the suitability of this material for a particular use or purpose. No warranty, either expressed or implied, is hereby made, nor do we give permission, inducement, or recommendations to practice any patented invention without a license. All data is offered for consideration, investigation and verification purposes only.