

Section 1: Material Identification

DREXEL 455 OIL 98.8

Product Name: Drexel 455 Oil 98.8

EPA Reg No.: 19713-396

CAS NO: 64741-88-4

Formula: Refined petroleum distillate

Company: Drexel Chemical Company

1700 Channel Avenue Memphis, TN 38106

Synonyms: Paraffin Oil

Identifiers:

EINECS: 232-455-8 **RTECS**: PY8047000

DOT information: See Section 14 for Transportation Information

Emergency Telephone Number:

CHEMTREC Drexel Chemical Co. Tel: 1-800-424-9300 901-774-4370

This product is an EPA FIFRA registered pesticide. Some of the classifications on this SDS are not the same as the FIFRA label. Certain sections of this SDS are superseded by federal law governed by EPA for a registered pesticide. Please see **Section 15: REGULATORY INFORMATION** for explanation.

Section 2: Hazard Identification

(As defined by the OSHA Hazard Communication Standard, 29)

GHS classification:

Health Hazards: Acute inhalation Category 4

Skin irritation Category 2
Eye irritation Category 2B

GHS label elements:

Signal Word: Warning

455 Oil 98.8 Page 1 of 8



Hazard Statements: Harmful if inhaled.

Causes skin irritation. Causes eye irritation.

Precautionary Statements:

Prevention: Avoid breathing vapors or mist. Use only outdoors or in a well-ventilated area.

Wash exposed skin thoroughly after handling. Use gloves chemically resistant to this material. Examples of preferred glove barrier materials include: Neoprene, Nitrile/butadiene rubber ("nitrile" or "NBR") or Polyvinyl chloride ("PVC" or "vinyl").

Response: If inhaled: Remove person to fresh air and keep comfortable for breathing. Call

Poison Control Center of Doctor if you feel unwell.

If on skin: Wash with plenty of water while removing contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Destroy contaminated leather items such as shoes, belts, and watchbands. If in eyes: Hold eye open and rinse slowly and gently with water for 15 to 20 minutes. Remove contact lenses, if present, after the first 5 minutes, then

continue rinsing eyes for at least 10 minutes. If eye irritation persists: get medical

attention, preferably from an ophthalmologist.

Storage: Store in a cool, dry, well ventilated, and secure area designated specifically for

pesticides and away from heat sources. Keep in original containers and keep containers closed when not in use. Do not store in excessive heat. Do not store

near children, food, foodstuffs, drugs or potable water supplies.

Disposal: Dispose of contents/container in accordance with your local or area regulatory

authorities.

Section 3: Composition Information

<u>Components</u>	CAS No.	<u>% By Wt.</u>	OSHA PEL	ACGIH TLV
Active Ingredient:				
Mineral Oil	64741-89-5	98.8%	N/Av	5 mg/m ³
Inert Ingredients:	N/A	1.2%	N/A	N/A

Section 4: First-Aid Measures

Eye Contact: Hold eye open and rinse slowly and gently with water for 15 to 20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eyes for at least 10 minutes. Obtain medical attention without delay, preferably from an ophthalmologist.

If Swallowed: Call a poison control center or doctor immediately for treatment advice. Wash out mouth with water. Do not induce vomiting unless told to do so by the poison control center or doctor. Do not give anything by mouth to an unconscious person. Have product label with you when calling a poison control center or doctor.

455 Oil 98.8 Page 2 of 8

Skin Contact: Immediately flush skin with plenty of water for 15 minutes while removing contaminated clothing and shoes. Wash skin with soap and water. Get medical attention if symptoms occur. Wash clothing before reuse. Destroy contaminated leather items such as shoes, belts, and watchbands.

If Inhaled: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth, if possible. Loosen tight clothing such as collar, tie, belt or waistband. Call a poison control center or doctor for further treatment advice.

Note to Physician: No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Section 5: Fire Fighting Measures

Fire Hazards: Low fire hazard. This material must be heated before ignition will occur. May be combustible at high temperature.

Flammability classification (OSHA 29 CFR 1910.1200): Non-combustible

Flash point: >350°F

Lower flammable limit (% by volume): N/Av Upper flammable limit (% by volume): N/Av

Fire Fighting Procedures: Keep people away. Isolate fire and deny unnecessary entry. Evacuate the area and fight the fire from upwind at a safe distance to avoid hazardous vapors or decomposition products. Dike and collect fire-extinguishing water to prevent environmental damage and excessive waste runoff.

Firefighting media: Use foam, carbon dioxide, or water fog when fighting fires involving this product. Do not use water jet, as this may spread burning material. Minimize the use of water to avoid environmental contamination. Contain all runoff.

Special Protective Equipment for Firefighters: Wear positive-pressure self-contained breathing apparatus (SCBA) and protective firefighting clothing (includes fire-fighting helmet, coat, trousers, boots, and gloves). Use full face shield and operate in positive pressure mode.

Hazardous Combustion Products: Carbon oxides (CO, CO₂), smoke and irritating vapors as products of incomplete combustion.

NFPA: Health: Flammability: Reactivity:

(Rating: 4-Extreme, 3-High, 2-Moderate, 1-Slight, 0-Insignificant)

Section 6: Accidental Release Measures

Steps to be taken if Material is Released or Spilled:

Contain spilled material if possible. Small spills: Sweep up. Collect in suitable and properly labeled containers.
 Large spills: Contact Drexel Chemical Co. for clean-up assistance. See Section 13, Disposal Considerations, for additional information.

Personal Precautions:

455 Oil 98.8 Page 3 of 8

Isolate area. Keep unnecessary and unprotected personnel from entering the area. Refer to Section 7, Handling, for
additional precautionary measures. Spilled material may cause a slipping hazard. Ventilate area of leak or spill. Use
appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal
Protection.

Environmental Precautions: Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12: Ecological Information.

Section 7: Handling and Storage

KEEP OUT OF REACH OF CHILDREN

Handling: General Handling: Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. Do not

swallow. Avoid breathing vapor. Use with adequate ventilation. Wear chemical protective equipment when handling. Keep away from heat, sparks and flame. See Section 8, Exposure Controls and Personal

Protection.

Storage: Store in a cool, dry area designated specifically for pesticides and away from heat sources. Keep in

original containers and keep containers closed when not in use. Do not store in excessive heat. Do not

store near children, food, foodstuffs, drugs or potable water supplies.

Section 8: Exposure Controls / Personal Protection

Exposure Limits: TLV: Refined Petroleum Distillate 5 mg/m³

Personal Protection:

Eye/Face Protection: Wear safety glasses with side shields or chemical splash goggles to prevent vapors or mists from entering the eyes. If using a full face shield, always use safety glasses or goggles along with the face shield to ensure adequate protection of the eyes.

Skin Protection: Wear coveralls, long-sleeved shirt and rubber boots. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task. Safety shower should be located in immediate work area. Remove contaminated clothing immediately, wash skin area with soap and water, and launder clothing before reuse or dispose of properly. Items which cannot be decontaminated, such as shoes, belts and watchbands, should be removed and disposed of properly.

Hand protection: Use gloves chemically resistant to this material. Examples of preferred glove barrier materials include: Neoprene, Nitrile/butadiene rubber ("nitrile" or "NBR") or Polyvinyl chloride ("PVC" or "vinyl").

Respiratory Protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. When handling in enclosed areas, when large quantities of mists are generated or prolonged exposure is possible in excess of the TLV, use a respirator with either an organic vapor-removing cartridge with a prefilter approved for pesticides (MSHA/NIOSH approval number prefix TC-23C) or a canister approved for pesticides (MSHA/NIOSH approval number prefix TC-14G).

Ingestion: Avoid ingestion of even very small amounts; do not consume or store food or tobacco in the work area; wash hands and face before smoking or eating.

Engineering Controls:

455 Oil 98.8 Page 4 of 8

Ventilation: When handling this product proper ventilation is required to maintain exposure below the TLV. Ventilate all transport vehicles prior to unloading. Facilities storing or utilizing this material should be equipped with an eyewash facility and safety shower.

Section 9: Physical and Chemical Properties

Physical State: Liquid
Color: Colorless

Odor: Slight petroleum

Odor threshold: N/Av Flash point: >350°F

Flammability: Not flammable

Upper/lower flammability or explosive limits: N/Av **Explosive properties:** N/Av Auto ignition temperature: N/Av Vapor pressure (mmHg): N/Av Vapor density: N/A **Evaporation rate:** N/Av **Boiling point:** N/A Vapor density (air = 1): N/A % Volatiles: N/Av Bulk density $(H_2O = 1)$: 0.85 g/cc Freezing point: N/A Solubility in water: Insoluble Partition coefficient (n-octanol/water): N/Av pH: N/A Viscosity: N/Av

Section 10: Stability and Reactivity

Stability/Instability: Thermally stable at typical use temperatures and in closed containers.

Conditions to Avoid: Avoid heat of open flame. Avoid high temperatures above 130°F (54.4°C). Avoid oxidizing agents.

Hazardous Polymerization: Will not occur under normal conditions of storage and use.

Thermal Decomposition: May release COx, smoke and irritating vapors when heated to decomposition.

Section 11: Toxicological Information

Data for a similar formulation:

Acute Toxicity:

Ingestion:

Oral LD50, (rat): >5,000 mg/kg

Dermal:

Dermal LD50, (rabbit): >2,000 mg/kg

455 Oil 98.8 Page 5 of 8

Inhalation:

Inhalation LC50, (rat): >3.02 mg/l

Eye Irritation (rabbit):

Mildly irritating

Skin Irritation (rabbit):

Mildly irritating

Sensitization Skin (guinea pig):

Non-sensitizer

Chronic Toxicity:

No known significant effects

Carcinogenicity:

Not listed as carcinogenic by IARC, NTP, ACGIH, or OSHA

Teratogenicity, mutagenicity, and other reproductive effects: None known

Section 12: Ecological Information

Ecotoxicological data:

ENVIRONMENTAL EFFECTS:

No known significant effects or critical hazards

Persistence and Degradability:

N/Av

Aquatic Toxicity:

N/Av

Bird Toxicity:

N/Av

Section 13: Disposal Considerations

If wastes and/or containers cannot be disposed of according to the product label directions, disposal of this material must be in accordance with your local or area regulatory authorities. This information presented below only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations. If the material as supplied becomes a waste, follow all applicable regional, national and local laws.

455 Oil 98.8 Page 6 of 8

Section 14: Transport Information

DOT: Non-regulated

NAFTA: Non-regulated

IMDG: Consult appropriate IMDG regulations for shipment requirements in the Maritime shipping modes.

ICAO/IATA: Consult appropriate ICAO/IATA regulations for shipment requirements in the Air modes.

Freight Description: Agricultural spray oil, liquid, n.o.s.

ERG Guide No.: 171

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

Section 15: Regulatory Information

OSHA Hazard Communication Standard:

- This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
- EPA FIFRA INFORMATION:

This chemical is a pesticide product registered by the United States Environmental Protection Agency and is subject to certain labeling requirements under federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS), and for workplace labels of non-pesticide chemical. The hazard information required on the pesticide label is listed out below. The pesticide label also includes other important information, including directions for use.

• EPA/CERCLA Reportable Quantity: None known

SARA/TITLE III:

- Sec. 302. Extremely Hazardous Substance Notification: This material is not known to contain any Extremely Hazardous Substances.
- Sec. 311/312. Hazard Categories: None
- Sec. 313. Toxic Chemical(s): This material is not known to contain any Toxic Chemical constituents.
- RCRA Waste Code: Not applicable

California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986):

• This product is not listed.

Toxic Substances Control Act (TSCA):

 All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.30

455 Oil 98.8 Page 7 of 8

Section 16: Other Information

Drexel Chemical Company recommends that each customer or recipient of this SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown below. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific SDSs, we are not and cannot be responsible for SDSs obtained from any source other than ourselves. If you have obtained an SDS from another source or if you are not sure that the SDS you have is current, please contact us for the most current version.

Date Revised: June 20, 2016 Supersedes: March 22, 2016

455 Oil 98.8 Page 8 of 8