MATERIAL SAFETY DATA SHEET

KALO, Inc. ● 13200 Metcalf Ave., Ste. 250 ● Overland Park, KS 66213 ● USA ● Toll Free 800-255-5196 ● 913-491-9125 ● FAX 913-491-9146 ● www.kalo.com

24 Hour Emergency Assistance C

CHEMTREC 1-800-424-9300

PRODUCT NAME: Hydro-Wet TG PRODUCT CODE: HYTG

I - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Hydro-Wet TG

PRODUCT CODE: HYTG

PRODUCT CLASS: Turf wetting agent

Date Prepared: 9/11/08

Prepared by: Safety Department

HMIS Codes	
Fire	0
Health	2
Reactivity	0
Protection	х

II - COMPOSITION/HAZARDOUS INGREDIENTS

OSHA Hazardous Components (29 CFR 1910.1200)

INGREDIENT - ND
PERCENT % - ND

OSHA PEL Respirable crystalline silica <.01% .1mg/m3 Ethylene glycol butyl ether <10% 25ppm

OCCUPATIONAL EXPOSURE LIMIT

ACGIH TLV Respirable crystalline silica <.01% .1mg/m3
Ethylene glycol butyl ether <10% 25ppm

III - HEALTH HAZARDS IDENTIFICATION

POTENTIAL HEALTH EFFECTS

Eyes: Ingestion:

May cause severe irritation or eye damage May cause headache, dizziness, nausea, vomiting, weakness,

blood disorders, or death.

Skin: Inhalation:

May cause severe irritation May cause irritation

Medical Conditions Aggravated: Disorders of the eyes, skin and lungs

Routes of Entry: Eye contact, skin contact, inhalation

Target Organs: Liver, lungs, kidneys

IV - FIRST AID

Eyes:

Hold eyelids open and flush with a steady, gentle stream of water for at least 15 minutes. Seek medical attention.

Skin

In case of contact, immediately wash with plenty of soap and water for at least 5 minutes. Seek medicalattention. Remove contaminated clothing and shoes. Clean contaminated clothing and shoes before re-use.

Inhalation:

Inhalation is not an expected route of exposure. If respiratory irritation or distress occurs remove victim to fresh air. Seek medical attention if respiratory irritation or distress continues.

Ingestion:

If victim is conscious and alert, give 1 to 2 glasses of water to drink. Do not give anything by mouth to an unconscious person . Seek medical attention. Do not leave victim unattended.

Antidotes:

Treat symptomatically. No specific antidote available.

Note to Physician:

All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

V - FIRE-FIGHTING MEASURES

Flashpoint: >200° Explosion Hazards: None known

Method: NA

Flammable Limits: Not established Fire Fighting Procedures: None

Autoignition Temperature: NA OSHA Flammability Class: NA

utoignition Temperature: NA

Extinguishing Media: Dry chemical, foam, CO2

Fire Fighting Equipment: Firefighters should wear NIOSH/MSHA approved self-contained breathing apparatus and full protective clothing.

VI - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Spill: Sweep, vacuum, or absorb with an inert absorbent for collection in an approved recovery drum for disposal. Wash area with water. Collect wash water for disposal. Always follow Federal, State and Local regulations regarding waste disposal.

PRODUCT NAME: Hydro-Wet TG PRODUCT CODE: HYTG

VII - HANDLING AND STORAGE

MINIMUM STORAGE TEMPERATURES: Will not freeze MAXIMUM STORAGE TEMPERATURES: Will not freeze

Handling: Avoid breathing vapors and mists. Avoid prolonged contact with skin and eyes.

Storage: Store in tightly closed original labeled containers. Store in a dry, well ventilated area away from ignition sources and incompatible materials.

VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

PERSONAL HYGIENE IS AN IMPORTANT EXPOSURE CONTROL MEASURE.

THE FOLLOWING GENERAL MEASURES SHOULD BE TAKEN WHEN WORKING OR HANDLING THIS MATERIAL.

Personal Protection

These recommendations provide general guidelines for handling this product. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application.

Skin

Skin contact should be minimized through the use of gloves and suitable long-sleeved clothing (i.e., shirts and pants)

Respiratory

Use NIOSH/MSHA approved respirator when exposure limits have been exceeded or are expected.

Eyes and Face

The use of chemical safety glasses with side shields or splash proof goggles when using this product is recommended. An emergency eye wash and safety shower should be accessible to the work area.

Work Hygienic Practices

- Do not store, use, and/or consume foods, beverages, tobacco products, or cosmetics in areas where this material is stored.
- **2)** Wash hands and face carefully before eating, drinking, using tobacco, applying cosmetics, or using the toilet.
- 3) Wash exposed skin promptly to remove accidental splashes of contact with this material.

IX - PHYSICAL AND CHEMICAL PROPERTIES

 Odor:
 mild solvent
 Density:
 47 lbs/cu ft

 Appearance:
 granule
 Particle Size:
 16/30 mesh US

 Color:
 tan
 Specific Gravity:
 NA

Color:tanSpecific Gravity:NApH:7.0 (1% solution)Viscosity:NA

Solubility in Water: NA

X - STABILITY AND REACTIVITY

Stable: Yes

Conditions to Avoid: Heat, open flame, spark

Hazardous Polymerization: Will not occur

Hazardous Decomposition: Oxides of carbon from burning Incompatible Materials: Strong oxidizers, strong bases

XI - TOXICOLOGICAL INFORMATION

Acute Oral:not establishedEye Irritation:not establishedAcute Dermal:not establishedSkin Irritation:not established

XII - DISPOSAL CONSIDERATIONS

Empty Container: Since empty packaging contain residues of the product, all labeled hazard precautions should be observed.

Always follow Federal, State and Local regulations regarding waste disposal.

XIII - TRANSPORTATION INFORMATION

DOT

REFER TO BILL OF LADING FOR CURRENT SHIPPING INFORMATION.

XIV - REGULATORY INFORMATION

SARA TITLE III (Superfund Amendments and Reauthorization Act)

302/311/312 Hazard Categories: Acute, chronic

304 CERCLA/313 Reportable Ingredients: Glycol ethers <10%

TSCA Status: All chemical substances in this product are listed in the TSCA inventory.

XV - OTHER INFORMATION

THE INFORMATION IN THIS MSDS IS GIVEN IN GOOD FAITH BASED ON OUR EXPERIENCE AND DATA PRESENTED IN VARIOUS TECHNICAL PUBLICATIONS. IT IS THE USERS RESPONSIBILITY TO DETERMINE THE SUITABILITY OF THIS INFORMATION FOR THE ADOPTION OF SAFETY PRECAUTIONS AS MAY BE NECESSARY. THE INFORMATION CONTAINED HEREIN IS FURNISHED WITHOUT WARRANTY OF ANY KIND.